

Copyright reserved. All rights reserved. This document is the property of miliet creating Pty Ltd. It is to be used for the specific project and site only. It is not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without the prior written consent of the author or the publisher.

LEGEND

01 ROADS
 02 DRIVEWAYS
 03 SIDEWALKS
 04 PATIO
 05 DECK
 06 POOL
 07 SPA
 08 SHED
 09 GARAGE
 10 CARPORT
 11 PORCH
 12 BALCONY
 13 TERRACE
 14 STAIRS
 15 RAMP
 16 FENCE
 17 WALL
 18 WINDOW
 19 DOOR
 20 ROOF
 21 CEILING
 22 FLOOR
 23 WALL
 24 PARTITION
 25 GLASS
 26 METAL
 27 WOOD
 28 CONCRETE
 29 BRICK
 30 STONE
 31 PLASTER
 32 PAINT
 33 TILE
 34 CARPET
 35 FLOORING
 36 LIGHTING
 37 MECHANICAL
 38 ELECTRICAL
 39 PLUMBING
 40 HVAC
 41 INSULATION
 42 SOUNDING
 43 GLAZING
 44 GLASS
 45 METAL
 46 WOOD
 47 CONCRETE
 48 BRICK
 49 STONE
 50 PLASTER
 51 PAINT
 52 TILE
 53 CARPET
 54 FLOORING
 55 LIGHTING
 56 MECHANICAL
 57 ELECTRICAL
 58 PLUMBING
 59 HVAC
 60 INSULATION
 61 SOUNDING
 62 GLAZING
 63 GLASS
 64 METAL
 65 WOOD
 66 CONCRETE
 67 BRICK
 68 STONE
 69 PLASTER
 70 PAINT
 71 TILE
 72 CARPET
 73 FLOORING
 74 LIGHTING
 75 MECHANICAL
 76 ELECTRICAL
 77 PLUMBING
 78 HVAC
 79 INSULATION
 80 SOUNDING
 81 GLAZING
 82 GLASS
 83 METAL
 84 WOOD
 85 CONCRETE
 86 BRICK
 87 STONE
 88 PLASTER
 89 PAINT
 90 TILE
 91 CARPET
 92 FLOORING
 93 LIGHTING
 94 MECHANICAL
 95 ELECTRICAL
 96 PLUMBING
 97 HVAC
 98 INSULATION
 99 SOUNDING
 100 GLAZING
 101 GLASS
 102 METAL
 103 WOOD
 104 CONCRETE
 105 BRICK
 106 STONE
 107 PLASTER
 108 PAINT
 109 TILE
 110 CARPET
 111 FLOORING
 112 LIGHTING
 113 MECHANICAL
 114 ELECTRICAL
 115 PLUMBING
 116 HVAC
 117 INSULATION
 118 SOUNDING
 119 GLAZING
 120 GLASS
 121 METAL
 122 WOOD
 123 CONCRETE
 124 BRICK
 125 STONE
 126 PLASTER
 127 PAINT
 128 TILE
 129 CARPET
 130 FLOORING
 131 LIGHTING
 132 MECHANICAL
 133 ELECTRICAL
 134 PLUMBING
 135 HVAC
 136 INSULATION
 137 SOUNDING
 138 GLAZING
 139 GLASS
 140 METAL
 141 WOOD
 142 CONCRETE
 143 BRICK
 144 STONE
 145 PLASTER
 146 PAINT
 147 TILE
 148 CARPET
 149 FLOORING
 150 LIGHTING
 151 MECHANICAL
 152 ELECTRICAL
 153 PLUMBING
 154 HVAC
 155 INSULATION
 156 SOUNDING
 157 GLAZING
 158 GLASS
 159 METAL
 160 WOOD
 161 CONCRETE
 162 BRICK
 163 STONE
 164 PLASTER
 165 PAINT
 166 TILE
 167 CARPET
 168 FLOORING
 169 LIGHTING
 170 MECHANICAL
 171 ELECTRICAL
 172 PLUMBING
 173 HVAC
 174 INSULATION
 175 SOUNDING
 176 GLAZING
 177 GLASS
 178 METAL
 179 WOOD
 180 CONCRETE
 181 BRICK
 182 STONE
 183 PLASTER
 184 PAINT
 185 TILE
 186 CARPET
 187 FLOORING
 188 LIGHTING
 189 MECHANICAL
 190 ELECTRICAL
 191 PLUMBING
 192 HVAC
 193 INSULATION
 194 SOUNDING
 195 GLAZING
 196 GLASS
 197 METAL
 198 WOOD
 199 CONCRETE
 200 BRICK
 201 STONE
 202 PLASTER
 203 PAINT
 204 TILE
 205 CARPET
 206 FLOORING
 207 LIGHTING
 208 MECHANICAL
 209 ELECTRICAL
 210 PLUMBING
 211 HVAC
 212 INSULATION
 213 SOUNDING
 214 GLAZING
 215 GLASS
 216 METAL
 217 WOOD
 218 CONCRETE
 219 BRICK
 220 STONE
 221 PLASTER
 222 PAINT
 223 TILE
 224 CARPET
 225 FLOORING
 226 LIGHTING
 227 MECHANICAL
 228 ELECTRICAL
 229 PLUMBING
 230 HVAC
 231 INSULATION
 232 SOUNDING
 233 GLAZING
 234 GLASS
 235 METAL
 236 WOOD
 237 CONCRETE
 238 BRICK
 239 STONE
 240 PLASTER
 241 PAINT
 242 TILE
 243 CARPET
 244 FLOORING
 245 LIGHTING
 246 MECHANICAL
 247 ELECTRICAL
 248 PLUMBING
 249 HVAC
 250 INSULATION
 251 SOUNDING
 252 GLAZING
 253 GLASS
 254 METAL
 255 WOOD
 256 CONCRETE
 257 BRICK
 258 STONE
 259 PLASTER
 260 PAINT
 261 TILE
 262 CARPET
 263 FLOORING
 264 LIGHTING
 265 MECHANICAL
 266 ELECTRICAL
 267 PLUMBING
 268 HVAC
 269 INSULATION
 270 SOUNDING
 271 GLAZING
 272 GLASS
 273 METAL
 274 WOOD
 275 CONCRETE
 276 BRICK
 277 STONE
 278 PLASTER
 279 PAINT
 280 TILE
 281 CARPET
 282 FLOORING
 283 LIGHTING
 284 MECHANICAL
 285 ELECTRICAL
 286 PLUMBING
 287 HVAC
 288 INSULATION
 289 SOUNDING
 290 GLAZING
 291 GLASS
 292 METAL
 293 WOOD
 294 CONCRETE
 295 BRICK
 296 STONE
 297 PLASTER
 298 PAINT
 299 TILE
 300 CARPET
 301 FLOORING
 302 LIGHTING
 303 MECHANICAL
 304 ELECTRICAL
 305 PLUMBING
 306 HVAC
 307 INSULATION
 308 SOUNDING
 309 GLAZING
 310 GLASS
 311 METAL
 312 WOOD
 313 CONCRETE
 314 BRICK
 315 STONE
 316 PLASTER
 317 PAINT
 318 TILE
 319 CARPET
 320 FLOORING
 321 LIGHTING
 322 MECHANICAL
 323 ELECTRICAL
 324 PLUMBING
 325 HVAC
 326 INSULATION
 327 SOUNDING
 328 GLAZING
 329 GLASS
 330 METAL
 331 WOOD
 332 CONCRETE
 333 BRICK
 334 STONE
 335 PLASTER
 336 PAINT
 337 TILE
 338 CARPET
 339 FLOORING
 340 LIGHTING
 341 MECHANICAL
 342 ELECTRICAL
 343 PLUMBING
 344 HVAC
 345 INSULATION
 346 SOUNDING
 347 GLAZING
 348 GLASS
 349 METAL
 350 WOOD
 351 CONCRETE
 352 BRICK
 353 STONE
 354 PLASTER
 355 PAINT
 356 TILE
 357 CARPET
 358 FLOORING
 359 LIGHTING
 360 MECHANICAL
 361 ELECTRICAL
 362 PLUMBING
 363 HVAC
 364 INSULATION
 365 SOUNDING
 366 GLAZING
 367 GLASS
 368 METAL
 369 WOOD
 370 CONCRETE
 371 BRICK
 372 STONE
 373 PLASTER
 374 PAINT
 375 TILE
 376 CARPET
 377 FLOORING
 378 LIGHTING
 379 MECHANICAL
 380 ELECTRICAL
 381 PLUMBING
 382 HVAC
 383 INSULATION
 384 SOUNDING
 385 GLAZING
 386 GLASS
 387 METAL
 388 WOOD
 389 CONCRETE
 390 BRICK
 391 STONE
 392 PLASTER
 393 PAINT
 394 TILE
 395 CARPET
 396 FLOORING
 397 LIGHTING
 398 MECHANICAL
 399 ELECTRICAL
 400 PLUMBING
 401 HVAC
 402 INSULATION
 403 SOUNDING
 404 GLAZING
 405 GLASS
 406 METAL
 407 WOOD
 408 CONCRETE
 409 BRICK
 410 STONE
 411 PLASTER
 412 PAINT
 413 TILE
 414 CARPET
 415 FLOORING
 416 LIGHTING
 417 MECHANICAL
 418 ELECTRICAL
 419 PLUMBING
 420 HVAC
 421 INSULATION
 422 SOUNDING
 423 GLAZING
 424 GLASS
 425 METAL
 426 WOOD
 427 CONCRETE
 428 BRICK
 429 STONE
 430 PLASTER
 431 PAINT
 432 TILE
 433 CARPET
 434 FLOORING
 435 LIGHTING
 436 MECHANICAL
 437 ELECTRICAL
 438 PLUMBING
 439 HVAC
 440 INSULATION
 441 SOUNDING
 442 GLAZING
 443 GLASS
 444 METAL
 445 WOOD
 446 CONCRETE
 447 BRICK
 448 STONE
 449 PLASTER
 450 PAINT
 451 TILE
 452 CARPET
 453 FLOORING
 454 LIGHTING
 455 MECHANICAL
 456 ELECTRICAL
 457 PLUMBING
 458 HVAC
 459 INSULATION
 460 SOUNDING
 461 GLAZING
 462 GLASS
 463 METAL
 464 WOOD
 465 CONCRETE
 466 BRICK
 467 STONE
 468 PLASTER
 469 PAINT
 470 TILE
 471 CARPET
 472 FLOORING
 473 LIGHTING
 474 MECHANICAL
 475 ELECTRICAL
 476 PLUMBING
 477 HVAC
 478 INSULATION
 479 SOUNDING
 480 GLAZING
 481 GLASS
 482 METAL
 483 WOOD
 484 CONCRETE
 485 BRICK
 486 STONE
 487 PLASTER
 488 PAINT
 489 TILE
 490 CARPET
 491 FLOORING
 492 LIGHTING
 493 MECHANICAL
 494 ELECTRICAL
 495 PLUMBING
 496 HVAC
 497 INSULATION
 498 SOUNDING
 499 GLAZING
 500 GLASS
 501 METAL
 502 WOOD
 503 CONCRETE
 504 BRICK
 505 STONE
 506 PLASTER
 507 PAINT
 508 TILE
 509 CARPET
 510 FLOORING
 511 LIGHTING
 512 MECHANICAL
 513 ELECTRICAL
 514 PLUMBING
 515 HVAC
 516 INSULATION
 517 SOUNDING
 518 GLAZING
 519 GLASS
 520 METAL
 521 WOOD
 522 CONCRETE
 523 BRICK
 524 STONE
 525 PLASTER
 526 PAINT
 527 TILE
 528 CARPET
 529 FLOORING
 530 LIGHTING
 531 MECHANICAL
 532 ELECTRICAL
 533 PLUMBING
 534 HVAC
 535 INSULATION
 536 SOUNDING
 537 GLAZING
 538 GLASS
 539 METAL
 540 WOOD
 541 CONCRETE
 542 BRICK
 543 STONE
 544 PLASTER
 545 PAINT
 546 TILE
 547 CARPET
 548 FLOORING
 549 LIGHTING
 550 MECHANICAL
 551 ELECTRICAL
 552 PLUMBING
 553 HVAC
 554 INSULATION
 555 SOUNDING
 556 GLAZING
 557 GLASS
 558 METAL
 559 WOOD
 560 CONCRETE
 561 BRICK
 562 STONE
 563 PLASTER
 564 PAINT
 565 TILE
 566 CARPET
 567 FLOORING
 568 LIGHTING
 569 MECHANICAL
 570 ELECTRICAL
 571 PLUMBING
 572 HVAC
 573 INSULATION
 574 SOUNDING
 575 GLAZING
 576 GLASS
 577 METAL
 578 WOOD
 579 CONCRETE
 580 BRICK
 581 STONE
 582 PLASTER
 583 PAINT
 584 TILE
 585 CARPET
 586 FLOORING
 587 LIGHTING
 588 MECHANICAL
 589 ELECTRICAL
 590 PLUMBING
 591 HVAC
 592 INSULATION
 593 SOUNDING
 594 GLAZING
 595 GLASS
 596 METAL
 597 WOOD
 598 CONCRETE
 599 BRICK
 600 STONE
 601 PLASTER
 602 PAINT
 603 TILE
 604 CARPET
 605 FLOORING
 606 LIGHTING
 607 MECHANICAL
 608 ELECTRICAL
 609 PLUMBING
 610 HVAC
 611 INSULATION
 612 SOUNDING
 613 GLAZING
 614 GLASS
 615 METAL
 616 WOOD
 617 CONCRETE
 618 BRICK
 619 STONE
 620 PLASTER
 621 PAINT
 622 TILE
 623 CARPET
 624 FLOORING
 625 LIGHTING
 626 MECHANICAL
 627 ELECTRICAL
 628 PLUMBING
 629 HVAC
 630 INSULATION
 631 SOUNDING
 632 GLAZING
 633 GLASS
 634 METAL
 635 WOOD
 636 CONCRETE
 637 BRICK
 638 STONE
 639 PLASTER
 640 PAINT
 641 TILE
 642 CARPET
 643 FLOORING
 644 LIGHTING
 645 MECHANICAL
 646 ELECTRICAL
 647 PLUMBING
 648 HVAC
 649 INSULATION
 650 SOUNDING
 651 GLAZING
 652 GLASS
 653 METAL
 654 WOOD
 655 CONCRETE
 656 BRICK
 657 STONE
 658 PLASTER
 659 PAINT
 660 TILE
 661 CARPET
 662 FLOORING
 663 LIGHTING
 664 MECHANICAL
 665 ELECTRICAL
 666 PLUMBING
 667 HVAC
 668 INSULATION
 669 SOUNDING
 670 GLAZING
 671 GLASS
 672 METAL
 673 WOOD
 674 CONCRETE
 675 BRICK
 676 STONE
 677 PLASTER
 678 PAINT
 679 TILE
 680 CARPET
 681 FLOORING
 682 LIGHTING
 683 MECHANICAL
 684 ELECTRICAL
 685 PLUMBING
 686 HVAC
 687 INSULATION
 688 SOUNDING
 689 GLAZING
 690 GLASS
 691 METAL
 692 WOOD
 693 CONCRETE
 694 BRICK
 695 STONE
 696 PLASTER
 697 PAINT
 698 TILE
 699 CARPET
 700 FLOORING
 701 LIGHTING
 702 MECHANICAL
 703 ELECTRICAL
 704 PLUMBING
 705 HVAC
 706 INSULATION
 707 SOUNDING
 708 GLAZING
 709 GLASS
 710 METAL
 711 WOOD
 712 CONCRETE
 713 BRICK
 714 STONE
 715 PLASTER
 716 PAINT
 717 TILE
 718 CARPET
 719 FLOORING
 720 LIGHTING
 721 MECHANICAL
 722 ELECTRICAL
 723 PLUMBING
 724 HVAC
 725 INSULATION
 726 SOUNDING
 727 GLAZING
 728 GLASS
 729 METAL
 730 WOOD
 731 CONCRETE
 732 BRICK
 733 STONE
 734 PLASTER
 735 PAINT
 736 TILE
 737 CARPET
 738 FLOORING
 739 LIGHTING
 740 MECHANICAL
 741 ELECTRICAL
 742 PLUMBING
 743 HVAC
 744 INSULATION
 745 SOUNDING
 746 GLAZING
 747 GLASS
 748 METAL
 749 WOOD
 750 CONCRETE
 751 BRICK
 752 STONE
 753 PLASTER
 754 PAINT
 755 TILE
 756 CARPET
 757 FLOORING
 758 LIGHTING
 759 MECHANICAL
 760 ELECTRICAL
 761 PLUMBING
 762 HVAC
 763 INSULATION
 764 SOUNDING
 765 GLAZING
 766 GLASS
 767 METAL
 768 WOOD
 769 CONCRETE
 770 BRICK
 771 STONE
 772 PLASTER
 773 PAINT
 774 TILE
 775 CARPET
 776 FLOORING
 777 LIGHTING
 778 MECHANICAL
 779 ELECTRICAL
 780 PLUMBING
 781 HVAC
 782 INSULATION
 783 SOUNDING
 784 GLAZING
 785 GLASS
 786 METAL
 787 WOOD
 788 CONCRETE
 789 BRICK
 790 STONE
 791 PLASTER
 792 PAINT
 793 TILE
 794 CARPET
 795 FLOORING
 796 LIGHTING
 797 MECHANICAL
 798 ELECTRICAL
 799 PLUMBING
 800 HVAC
 801 INSULATION
 802 SOUNDING
 803 GLAZING
 804 GLASS
 805 METAL
 806 WOOD
 807 CONCRETE
 808 BRICK
 809 STONE
 810 PLASTER
 811 PAINT
 812 TILE
 813 CARPET
 814 FLOORING
 815 LIGHTING
 816 MECHANICAL
 817 ELECTRICAL
 818 PLUMBING
 819 HVAC
 820 INSULATION
 821 SOUNDING
 822 GLAZING
 823 GLASS
 824 METAL
 825 WOOD
 826 CONCRETE
 827 BRICK
 828 STONE
 829 PLASTER
 830 PAINT
 831 TILE
 832 CARPET
 833 FLOORING
 834 LIGHTING
 835 MECHANICAL
 836 ELECTRICAL
 837 PLUMBING
 838 HVAC
 839 INSULATION
 840 SOUNDING
 841 GLAZING
 842 GLASS
 843 METAL
 844 WOOD
 845 CONCRETE
 846 BRICK
 847 STONE
 848 PLASTER
 849 PAINT
 850 TILE
 851 CARPET
 852 FLOORING
 853 LIGHTING
 854 MECHANICAL
 855 ELECTRICAL
 856 PLUMBING
 857 HVAC
 858 INSULATION
 859 SOUNDING
 860 GLAZING
 861 GLASS
 862 METAL
 863 WOOD
 864 CONCRETE
 865 BRICK
 866 STONE
 867 PLASTER
 868 PAINT
 869 TILE
 870 CARPET
 871 FLOORING
 872 LIGHTING
 873 MECHANICAL
 874 ELECTRICAL
 875 PLUMBING
 876 HVAC
 877 INSULATION
 878 SOUNDING
 879 GLAZING
 880 GLASS
 881 METAL
 882 WOOD
 883 CONCRETE
 884 BRICK
 885 STONE
 886 PLASTER
 887 PAINT
 888 TILE
 889 CARPET
 890 FLOORING
 891 LIGHTING
 892 MECHANICAL
 893 ELECTRICAL
 894 PLUMBING
 895 HVAC
 896 INSULATION
 897 SOUNDING
 898 GLAZING
 899 GLASS
 900 METAL
 901 WOOD
 902 CONCRETE
 903 BRICK
 904 STONE
 905 PLASTER
 906 PAINT
 907 TILE
 908 CARPET
 909 FLOORING
 910 LIGHTING
 911 MECHANICAL
 912 ELECTRICAL
 913 PLUMBING
 914 HVAC
 915 INSULATION
 916 SOUNDING
 917 GLAZING
 918 GLASS
 919 METAL
 920 WOOD
 921 CONCRETE
 922 BRICK
 923 STONE
 924 PLASTER
 925 PAINT
 926 TILE
 927 CARPET
 928 FLOORING
 929 LIGHTING
 930 MECHANICAL
 931 ELECTRICAL
 932 PLUMBING
 933 HVAC
 934 INSULATION
 935 SOUNDING
 936 GLAZING
 937 GLASS
 938 METAL
 939 WOOD
 940 CONCRETE
 941 BRICK
 942 STONE
 943 PLASTER
 944 PAINT
 945 TILE
 946 CARPET
 947 FLOORING
 948 LIGHTING
 949 MECHANICAL
 950 ELECTRICAL
 951 PLUMBING
 952 HVAC
 953 INSULATION
 954 SOUNDING
 955 GLAZING
 956 GLASS
 957 METAL
 958 WOOD
 959 CONCRETE
 960 BRICK
 961 STONE
 962 PLASTER
 963 PAINT
 964 TILE
 965 CARPET
 966 FLOORING
 967 LIGHTING
 968 MECHANICAL
 969 ELECTRICAL
 970 PLUMBING
 971 HVAC
 972 INSULATION
 973 SOUNDING
 974 GLAZING
 975 GLASS
 976 METAL
 977 WOOD
 978 CONCRETE
 979 BRICK
 980 STONE
 981 PLASTER
 982 PAINT
 983 TILE
 984 CARPET
 985 FLOORING
 986 LIGHTING
 987 MECHANICAL
 988 ELECTRICAL
 989 PLUMBING
 990 HVAC
 991 INSULATION
 992 SOUNDING
 993 GLAZING
 994 GLASS
 995 METAL
 996 WOOD
 997 CONCRETE
 998 BRICK
 999 STONE
 1000 PLASTER
 1001 PAINT
 1002 TILE
 1003 CARPET
 1004 FLOORING
 1005 LIGHTING
 1006 MECHANICAL
 1007 ELECTRICAL
 1008 PLUMBING
 1009 HVAC
 1010 INSULATION
 1011 SOUNDING
 1012 GLAZING
 1013 GLASS
 1014 METAL
 1015 WOOD
 1016 CONCRETE
 1017 BRICK
 1018 STONE
 1019 PLASTER
 1020 PAINT
 1021 TILE
 1022 CARPET
 1023 FLOORING
 1024 LIGHTING
 1025 MECHANICAL
 1026 ELECTRICAL
 1027 PLUMBING
 1028 HVAC
 1029 INSULATION
 1030 SOUNDING
 1031 GLAZING
 1032 GLASS
 1033 METAL
 1034 WOOD
 1035 CONCRETE
 1036 BRICK
 1037 STONE
 1038 PLASTER
 1039 PAINT
 1040 TILE
 1041 CARPET
 1042 FLOORING
 1043 LIGHTING
 1044 MECHANICAL
 1045 ELECTRICAL
 1046 PLUMBING
 1047 HVAC
 1048 INSULATION
 1049 SOUNDING
 1050 GLAZING
 1051 GLASS
 1052 METAL
 1053 WOOD
 1054 CONCRETE
 1055 BRICK
 1056 STONE
 1057 PLASTER
 1058 PAINT
 1059 TILE
 1060 CARPET
 1061 FLOORING
 1062 LIGHTING
 1063 MECHANICAL
 1064 ELECTRICAL
 1065 PLUMBING
 1066 HVAC
 1067 INSULATION
 1068 SOUNDING
 1069 GLAZING
 1070 GLASS
 1071 METAL
 1072 WOOD
 1073 CONCRETE
 1074 BRICK
 1075 STONE
 1076 PLASTER
 1077 PAINT
 1078 TILE
 1079 CARPET
 1080 FLOORING
 1081 LIGHTING
 1082 MECHANICAL
 1083 ELECTRICAL
 1084 PLUMBING
 1085 HVAC
 1086 INSULATION
 1087 SOUNDING
 1088 GLAZING
 1089 GLASS
 1090 METAL
 1091 WOOD
 1092 CONCRETE
 1093 BRICK
 1094 STONE
 1095 PLASTER
 1096 PAINT
 1097 TILE
 1098 CARPET
 1099 FLOORING
 1100 LIGHTING
 1101 MECHANICAL
 1102 ELECTRICAL
 1103 PLUMBING
 1104 HVAC
 1105 INSULATION
 1106 SOUNDING
 1107 GLAZING
 1108 GLASS
 1109 METAL
 1110 WOOD
 1111 CONCRETE
 1112 BRICK
 1113 STONE
 1114 PLASTER
 1115 PAINT
 1116 TILE
 1117 CARPET
 1118 FLOORING
 1119 LIGHTING
 1120 MECHANICAL
 1121 ELECTRICAL
 1122 PLUMBING
 1123 HVAC
 1124 INSULATION
 1125 SOUNDING
 1126 GLAZING
 1127 GLASS
 1128 METAL
 1129 WOOD
 1130 CONCRETE
 1131 BRICK
 1132 STONE
 1133 PLASTER
 1134 PAINT
 1135 TILE
 1136 CARPET
 1137 FLOORING
 1138 LIGHTING
 1139 MECHANICAL
 1140 ELECTRICAL
 1141 PLUMBING
 1142 HVAC
 1143 INSULATION
 1144 SOUNDING
 1145 GLAZING
 1146 GLASS
 1147 METAL
 1148 WOOD
 1149 CONCRETE
 1150 BRICK
 1151 STONE
 1152 PLASTER
 1153 PAINT
 1154 TILE
 1155 CARPET
 1156 FLOORING
 1157 LIGHTING
 1158 MECHANICAL
 1159 ELECTRICAL
 1160 PLUMBING
 1161 HVAC
 1162 INSULATION
 1163 SOUNDING
 1164 GLAZING
 1165 GLASS
 1166 METAL
 1167 WOOD
 1168 CONCRETE
 1169 BRICK
 1170 STONE
 1171 PLASTER
 1172 PAINT
 1173 TILE
 1174 CARPET
 1175 FLOORING
 1176 LIGHTING
 1177 MECHANICAL
 1178 ELECTRICAL
 1179 PLUMBING
 1180 HVAC
 1181 INSULATION
 1182 SOUNDING
 1183 GLAZING
 1184 GLASS
 1185 METAL
 1186 WOOD
 1187 CONCRETE



ATTACHMENT 5

COASTAL HAZARD ASSESSMENT

R1569 Rev 1

August 2021

Rowe Group

**Onslow Township Village
Coastal Hazard Risk Management & Adaptation
Planning**

marinas

boat harbours

canals

breakwaters

jetties

seawalls

dredging

reclamation

climate change

waves

currents

tides

flood levels

water quality

siltation

erosion

rivers

beaches

estuaries

www.coastsandports.com.au

m p rogers & associates pl

creating better coasts and ports

Suite 1, 128 Main Street, Osborne Park, WA 6017

p: +618 9254 6600

e: admin@coastsandports.com.au

w: www.coastsandports.com.au

K1905, Report R1569 Rev 1

Record of Document Revisions

Rev	Purpose of Document	Prepared	Reviewed	Approved	Date
A	Draft for MRA review	M Peterson	M Rogers	M Rogers	03/08/21
0	Issued to Client	M Peterson	M Rogers	M Rogers	03/08/21
1	Updated with Client Comments	M Peterson			31/08/21

Form 035 18/06/2013

Limitations of this Document

This document has been prepared for use by the Client in accordance with the agreement between the Client and M P Rogers & Associates Pty Ltd. This agreement includes constraints on the scope, budget and time available for the services. The consulting services and this document have been completed with the degree of skill, care and diligence normally exercised by members of the engineering profession performing services of a similar nature. No other warranty, expressed or implied, is made as to the accuracy of the data and professional advice included. This document has not been prepared for use by parties other than the Client and its consulting advisers. It may not contain sufficient information for the purposes of other parties or for other uses.

M P Rogers & Associates takes no responsibility for the completeness or form of any subsequent copies of this document. Copying this document without the permission of the Client or M P Rogers & Associates Pty Ltd is not permitted.

Table of Contents

1. Introduction	1
1.1 State Coastal Planning Policy (SPP 2.6)	1
2. Context	3
2.1 Purpose	3
2.2 Objectives	3
2.3 Scope	3
2.4 The Site	5
3. Coastal Hazards	8
3.1 Coastal Erosion Hazard	8
3.2 Coastal Inundation Hazard	8
4. Coastal Hazard Adaptation & Mitigation Strategy	10
4.1 Coastal Hazard Risk	10
4.2 Mitigation Strategy	10
5. Implementation Plan	11
5.1 Planning & Initial Construction	11
5.2 Operation Over the Resort Design Life	11
5.3 Resort Handover	11
5.4 Monitoring & Review	12
5.5 Review of CHRMAP Guidelines	12
6. Summary	14
7. References	15
8. Appendices	16
Appendix A Coastal Erosion Hazard Map	17
Appendix B Coastal Inundation Hazard Map	19

Table of Figures

Figure 1.1	Approximate Proposed Location of Development	1
Figure 2.1	Risk Management & Adaptation Process Flow Chart (WAPC 2019)	4
Figure 2.2	Preliminary Masterplan (Provided by Milieu Creative 2021)	6

Table of Tables

Table 3.1	Total Coastal Erosion Hazard Allowances	8
Table 3.2	Inundation Levels	9
Table 5.1	Implementation Plan Summary – Planning & Initial Construction Stage	11
Table 5.2	Implementation Plan Summary – Operation Over the Infrastructure Design Life	11
Table 5.3	Implementation Plan Summary – Resort Handover	12
Table 5.4	Shoreline Monitoring Plan – When Required	12

1. Introduction

Mineral Resources Limited (MRL) are investigating the feasibility of developing a resort on Lot 300 Back Beach Road, Onslow. It would be used by their fly in fly out (FIFO) workers. As part of this process, a Development Application is required. To assist with the progression of the Development Application MRL engaged Rowe Group (Rowe) to coordinate a consultant team. The proposed development known as Onslow Township Village, is located on the coastline of Beadon Point to the northwest of the Onslow Town Centre (refer Figure 1.1).



Figure 1.1 Approximate Proposed Location of Development

As the development is located on the coast, an assessment of the possible impacts of coastal hazards on the development is required to inform the development application. This assessment of the coastal hazards will be completed through the Coastal Hazard Risk Management and Adaptation Planning (CHRMAP) guidelines in the State Coastal Planning Policy. To complete the CHRMAP, Rowe engaged specialist coastal and port engineers M P Rogers & Associates Pty Ltd.

1.1 State Coastal Planning Policy (SPP 2.6)

Within Western Australia, State Planning Policy 2.6: State Coastal Planning Policy (SPP2.6; WAPC 2019) provides guidance for land use and development decision-making within the coastal zone, including the establishment of coastal foreshore reserves to protect, conserve and enhance coastal values. SPP2.6 also provides guidance on the assessment of coastal hazard risks for assets located in close proximity to the coast.

The objectives of SPP2.6 are wide ranging, however a key component of the policy is the identification of appropriate areas for the sustainable use of the coast. This includes use for recreational, tourism and commercial purposes, which are relevant to the intended future development of the Onslow Township Village.

The guidance on the assessment of coastal hazard risk is provided within SPP2.6 in the form of a methodology to assess the potential extent of coastal hazard impacts, as well as for the development of a CHRMAP report. Further details in this regard are also provided in the CHRMAP Guidelines (WAPC 2019).

The key requirement of CHRMAP is to develop a risk based adaptation framework for assets that could be at risk of impact by coastal hazards over the relevant planning timeframe. Importantly, the balance of these risks needs to be considered with reference to the expected lifetime of the relevant assets.

2. Context

2.1 Purpose

The potential vulnerability of the coastline and the subsequent risk to the community, economy and environment needs to be considered for any coastal development.

SPP2.6 requires that the responsible management authority completes CHRMAP where an existing or proposed development may be at risk from coastal hazards over the planning timeframe. The main purpose of the CHRMAP is to define areas of the coastline which could be vulnerable to coastal hazards and to outline the intended approach to the monitoring and management of these hazards where required.

CHRMAP can be a powerful planning tool to help provide clarity to existing and future developers, users, managers or custodians of the coastline. This is done by defining levels of risk exposure, management practices and adaptation techniques that the management authority considers acceptable in response to the present and future risks posed by coastal hazards.

Specifically, the purpose of this CHRMAP is as follows:

- Determine the specific extent of coastal hazards in relation to the Onslow Township Village development.
- Determine the coastal hazard risks associated with the Onslow Township Village development.
- Establish the basis for present and future risk management and adaptation.
- Provide guidance on appropriate management and adaptation planning for the future, including monitoring.

2.2 Objectives

The key objectives of this CHRMAP are as follows:

- Inform the development of the Onslow Township Village.
- Ensure that MRL, Rowe and key stakeholders understand the potential likelihood of the development being impacted by coastal hazards over the 100 year planning timeframe.
- Outline the required coastal adaptation approach in an Implementation Plan that is acceptable to MRL, Rowe and key stakeholders.

2.3 Scope

The CHRMAP Guidelines (WAPC 2019) provide a specific framework for the preparation of a CHRMAP. This is outlined in the flowchart presented in Figure 2.1 which shows the risk management process adapted to coastal planning.




Figure 2.1 Risk Management & Adaptation Process Flow Chart (WAPC 2019)

As presented in the flowchart, the process for the development of a meaningful CHRMAP process requires a number of fundamental inputs. These inputs enable the assessment and analysis of

risk, which should ultimately be informed by input received from key stakeholders, to help shape the subsequent adaptation strategies.

The development of the Onslow Township Village will require an adaptation plan that is acceptable to all stakeholders. As a result, the approach that has been taken for this plan is to develop a management methodology that allows for flexibility into the future, given the inherent uncertainties associated with long term coastal behaviour.

The development of the adaptation plan will be informed by the assessment of the coastal erosion and inundation hazards at the site. The identification of the coastal erosion and inundation hazards for the Onslow Township Village is presented within Section 3 of this report.

This CHRMAP will consider the potential risks posed by coastal hazards over a range of horizons covering the 100 year planning timeframe. This planning timeframe is required by SPP2.6 for development on the coast, though it is noted that the lifetime of a structure on the coastline is unlikely to span this 100 year planning timeframe without requiring reconstruction.

Based on the results of the risk assessment, risk mitigation strategies will be developed, where required, in order to provide a framework for future management. However, it is important to realise that the risk assessment will be based on the outcomes of the coastal vulnerability assessment, which, by their nature, are justifiably conservative. This is due to the uncertainty around coastal dynamics when predicting impacts over long timeframes. As a result, the framework for future risk management strategies should be considered to be a guide of future requirements.

2.4 The Site

The Onslow Township Village is planned to be located on Lot 300 Back Beach Road in Onslow. Lot 300 is located adjacent to the coast on Beadon Point and as such provides easy access to both the beach and Onslow's town centre. The highest part of the site is located in the northeast corner with the remainder of the site slopping towards the west and south. The south western portion of the site is culturally significant to the local Thalanyji people and as such will not be developed.

A preliminary masterplan for the proposed development prepared by Milieu Creative is presented in Figure 2.2.

The preliminary masterplan includes the following.

- A culturally significant area in the south western portion of the site which is not being developed.
- Approximately 500 accommodation pods.
- Recreational facilities including an oval, a pool, a gym and a recreation room.
- Administrative and service facilities including a restaurant, a medical centre and administration.

3. Coastal Hazards

The Shire of Ashburton (Shire) engaged Cardno to complete a CHRMAP report for the Onslow Coast (Cardno 2017). As part of this process Cardno completed a coastal hazard assessment of the Onslow Coast which includes the coastal area of the Onslow Township Village (Cardno 2016). The methods, assumptions and results of the coastal hazard assessment are detailed in Cardno (2016), a summary is provided below for context.

3.1 Coastal Erosion Hazard

At the Onslow Township Village site, Cardno calculated the Horizontal Shoreline Datum (HSD) to be the 2.4 mAHD contour.

As part of their assessment Cardno broke the Onslow Coast into a number of sections, the Onslow Township Village is located across sections 1 and 2. The extent of erosion in a 100 year Average Recurrence Interval (ARI) storm event was calculated by Cardno to be 19 m behind the HSD in section 1 and 7 m behind the HSD in section 2.

Using historical aerial images of the coastline between 1969 and 2015, the long term trends of beach accretion and erosion were examined. Cardno adopted an historical accretion rate of 0.6 m/year for section 1 and an historical erosion rate of 0.03 m/year for section 2. To adopt a conservative approach Cardno adopted an accretion rate of 0.2 m/year for section 1. SPP2.6 allows for half of the long term accretion trend to be used in the calculation of the erosion hazard. As such Cardno adopted long term shoreline movement allowances of 0.1m/year accretion for section 1 and 0.03 m/year erosion for section 2 over the 100 year planning horizon.

The potential impacts of sea level rise due to climate change was also examined by Cardno. Cardno adopted a recession of 0.9 m/year over the 100 year planning horizon.

SPP2.6 also recommends an allowance of a further 0.2 m/year to account for uncertainty.

The total coastal erosion hazard allowances determined by Cardno are displayed in Table 3.1.

Table 3.1 Total Coastal Erosion Hazard Allowances

Section	2040	2070	2110
1	49 m	79 m	119 m
2	41 m	75 m	120 m

Note1: Values determined from Cardno (2016).

A coastal erosion hazard map of the Onslow Township Village site has been prepared using the values determined by Cardno and is included in Appendix A.

3.2 Coastal Inundation Hazard

The State Coastal Planning Policy requires consideration of the inundation of the 0.2% annual probability of the ocean flood level being reached or exceeded in any one year. This is the same probability as the 500 year ARI ocean storm surge event occurring in any one year. Due to the

location of the Onslow Township Village the 500 year ARI event is assumed to be caused by a Tropical Cyclone event.

To determine the 500 year ARI water level event Cardno conducted a Monte Carlo study comprising 10,000 years of synthetic cyclone tracks. These cyclones were then ranked, and the severe events modelled using Delft3d to determine the water levels for Onslow. An extreme analysis of the water levels was conducted to determine the water level corresponding to the 500 year ARI event.

This water level was then increased using an allowance for wave set up and an allowance for sea level rise over the 100 year planning horizon. The resulting inundation levels determined by Cardno are displayed in Table 3.2.

Table 3.2 Inundation Levels

Year	Inundation Level
2040	3.51 mAHD
2070	3.85 mAHD
2110	4.57 mAHD

Note1: Values determined from Cardno (2016).

A coastal inundation hazard map of the Onslow Township Village Site has been prepared using the inundation levels determined by Cardno and the most recent available survey of the site. This is included in Appendix B. It should be noted that the Cardno assessment included fluvial inundation of the site. This has been ignored in this assessment as it is assumed that as part of the development appropriate drainage will be installed, preventing this fluvial inundation.

4. Coastal Hazard Adaptation & Mitigation Strategy

4.1 Coastal Hazard Risk

Based on the coastal hazard allowances determined by Cardno (2016) and shown in the coastal hazard maps included in Appendices A and B, there is a minimal risk to the key assets of the proposed Onslow Township Village development. All of the development's assets are located outside of the Inundation allowance. The only area likely to be affected by inundation is the culturally significant area which will not be developed.

There are approximately eight of the accommodation pods that have approximately 10% of their footprint within the erosion hazard allowance. Given the low likelihood of the coastal erosion reaching this position, the low consequence if it does and the high adaptive capacity of the accommodation pods the coastal erosion hazard risk for these assets was determined to be very low.

As such the coastal erosion risk to all of the assets has been determined to be minimal and has been excluded from the adaptation planning. However, an allowance of 30 m for a foreshore reserve to provide a recreation area has been included in the coastal erosion hazard map. When this additional allowance is added to the 2110 erosion hazard allowance approximately 32 of the accommodation pods and part of the oval fall within this area. As such adaptation planning has been completed for these assets.

4.2 Mitigation Strategy

The overarching strategy for the Onslow Township Village development is a combined strategy of avoid and managed retreat / removal. The majority of the development's assets will be located outside of the required foreshore reserve area thus avoiding the coastal hazards. The assets that had to be located within the required future foreshore reserve will be subject to managed retreat.

MRA have been advised that the 500 accommodation pod resort has a proposed lifespan of approximately 30 years which will coincide with MRL's nearby mining operations. At the end of this 30 year period the development will be handed over to the Thalanyji people and will likely be converted into a more traditional tourist resort. As part of this handover to the Thalanyji people the number of accommodation pods will be reduced to suit the erosion situation and forecasts at that time.

As such by 2055 a portion of the accommodation pods will likely have been removed essentially enacting a managed retreat / removal strategy. The accommodation pods located within the foreshore area will be among the pods that are likely to be removed. The coastal erosion hazard map included in Appendix A includes an erosion line for 2070 which is located between 41 and 45 m seawards of the 2110 line. This demonstrates that there will be ample room to fit a reserve area for recreation throughout the 100 year timeframe.

In addition to the managed retreat / removal of the accommodation pods, the pods will also be designed to be easily relocatable. As such if the coastal hazard risks change the accommodation pods can easily be relocated to a safer location.

When the development is handed over to the Thalanyji people in approximately 30 years a portion of the site may need to be ceded to the Shire to ensure that an adequate foreshore reserve is maintained.

5. Implementation Plan

The risk adaptation and mitigation strategies outlined in Section 4 set out the general proposed coastal management approach for the development. Direct guidance on when, what, how and by who these processes will be completed is provided within this implementation plan. For ease of reference, these details have been broken down to outline the requirements for each stage of the project and / or asset life.

5.1 Planning & Initial Construction

Where possible assets will be located in areas outside of the identified coastal hazard areas and the reserve for recreation over a 100 year planning horizon. The assets that cannot be located outside of these areas will need to be designed to be easily relocatable to allow managed retreat.

Table 5.1 Implementation Plan Summary – Planning & Initial Construction Stage

Requirement	Timing	Responsibility
Acceptance of coastal hazard risks where avoidance was not possible.	Planning Stage	MRL
Appropriate design of assets to ensure that risks are managed as best as possible.	Planning & Design Phase	MRL (supported by design team)

5.2 Operation Over the Resort Design Life

Over the design life of the resort there will be a requirement to monitor the shoreline to ascertain whether the risk to assets is increasing. Further details of the monitoring requirements are outlined in Section 5.4. This monitoring will be the responsibility of the MRL before handover and the Thalanyji people afterwards.

Table 5.2 Implementation Plan Summary – Operation Over the Infrastructure Design Life

Requirement	Timing	Responsibility
Monitoring of coastal hazard risk to assess if risk becomes untenable and assets need to be relocated. (Refer Section 5.4)	Operation over design life	MLR / Thalanyji People

5.3 Resort Handover

At the end of the initial 30 year period the resort will be handed over to the Thalanyji people and at this time a portion of the accommodation pods may need to be removed. During this process the pods that are currently located within the 2110 reserve for recreation area would be removed (refer Appendix A). At this time it may be necessary for the most seaward portion of the site to be ceded to the Shire to ensure that an adequate foreshore reserve can be maintained throughout the remainder of the 100 year planning horizon.

It is recommended that at this time an updated CHMRAP be completed to quantify the risk to any remaining and / or proposed additional assets.

Table 5.3 Implementation Plan Summary – Resort Handover

Requirement	Timing	Responsibility
Complete a revised coastal hazard risk assessment to quantify the risk level at that time.	Resort Handover	MRL / Thalanyji People
Remove portion of the accommodation pods.	Resort Handover	MRL

5.4 Monitoring & Review

Coastal monitoring and review are essential in order to track changes to the shoreline over time. Whilst the coastal hazards discussed in Section 3 provide an indication of the potential changes to the shoreline (and incorporate a justifiable level of conservatism), the system is inherently complex, and the actual shoreline response could be different to that presented.

Should the HSD or coastal vegetation line retreat to within 30 m of the cadastral boundary of Lot 300, then the following shoreline monitoring plan should be initiated.

The shoreline monitoring should be completed using a combination of onsite measurements and photo-monitoring as well as review of aerial photography captured by Landgate and others. The recommended monitoring plan for the site is presented in Table 5.4 below. The responsibility for the shoreline monitoring will rest with the development owner at that time.

Table 5.4 Shoreline Monitoring Plan – When Required

Monitoring Event	Timing	Responsibility
Photo Monitoring.	Yearly	MRL / Thalanyji People
Review of aerial imagery.	Every 5 years	MRL / Thalanyji People
Detailed survey of the shoreline and Development.	Following severe erosion events OR Following the retreat of the shoreline (HSD) to within 20 m of an asset	MRL / Thalanyji People

5.5 Review of CHRMAP Guidelines

Should the State Government guidance for the determination of the required coastal hazard allowances change as a result of new information becoming available, the Coastal Hazard Assessment and this CHRMAP should also be reviewed. This is especially the case for information regarding climate change and projected sea level rise, however this may also apply

for the calculation of inundation allowances. The responsibility for both of these actions would rest with the MRL prior to handover and the Thalanyji People afterwards.

6. Summary

MRL wish to develop the Onslow Township Village on Lot 300 Back Beach Road, Onslow.

Rowe engaged MRA to conduct a CHRMAP assessment of the proposed Onslow Township Village development to inform a development application. This CHRMAP has been completed to provide guidance on the coastal hazards and the required adaptation and management actions associated with the proposed development. It has been completed in line with the recommendations of SPP2.6 and WAPC (2019).

Coastal hazards determined from Cardno's coastal hazard assessment for Onslow show that there is a very low risk of coastal hazards adversely impacting the proposed development. However, with the addition of a 30 m wide foreshore reserve area for recreation, a number of the accommodation pods included in the initial development may be within the foreshore reserve after about 30 years. As such a managed retreat / remove strategy will be implemented for these assets. All other assets maintain an avoid adaptation strategy. After approximately 30 years MRL will hand over the development to the Thalanyji people and in the process a portion of the accommodation pods may be removed. In this way the managed retreat / removal adaptation strategy will be implemented, and an adequate foreshore reserve maintained.

7. References


- Cardno 2016. *Coastal Hazard Assessment CHRMAP for the Onslow Coast*. Prepared for the Shire of Ashburton, Western Australia.
- Cardno 2017. *Coastal Hazard Risk Management & Adaptation Plan CHRMAP For the Onslow Coast*. Prepared for the Shire of Ashburton, Western Australia
- Department of Transport 2010. *Sea Level Change in Western Australia – Application to Coastal Planning*. Prepared by the Department of Transport, Western Australia.
- Milieu Creative 2021. *Onslow Township Resort Lot 300 Back Beach Road, Onslow Proposed Masterplan Presentation*. Prepared for Mineral Resources Limited.
- Standards Australia 2009. *AS/NZS ISO 31000:2009 Risk Management – Principles and Guidelines*.
- WAPC, 2013. *Statement of Planning Policy No. 2.6 – State Coastal Planning Policy*. Western Australian State Government, Perth.
- WAPC 2019. *Coastal Hazard Risk Management and Adaptation Planning Guidelines*. Government of Western Australia, Perth.

8. Appendices

Appendix A Coastal Erosion Hazard Map

Appendix B Coastal Inundation Hazard Map

Appendix A Coastal Erosion Hazard Map



- LEGEND:**
- HORIZONTAL SHORELINE DATUM
 - 2070 COASTAL EROSION ALLOWANCE
 - 2110 COASTAL EROSION ALLOWANCE
 - 2110 PUBLIC RESERVE ALLOWANCE (30m)
 - - - LOT 300 BOUNDARY

- NOTES:**
1. AERIAL PHOTOGRAPH PROVIDED BY LANDGATE TAKEN IN FEBRUARY 2020.
 2. HORIZONTAL SHORELINE DATUM, 2070 AND 2110 COASTAL EROSION ALLOWANCE TAKEN FROM CARDNO COASTAL HAZARD ASSESSMENT (2016).
 3. SITE PLAN PROVIDED BY MILIEU CREATIVE IN AUGUST 2021.

AT CORRECT SCALE THIS IS 100 mm

AT CORRECT SCALE THIS IS 100 mm

COASTAL EROSION HAZARD ALLOWANCE
 ONSLOW TOWNSHIP VILLAGE

DRAWN M. PETERSON
CHECKED M. ROGERS

Suite 1, 128 Main Street
 Osborne Park 6017
 Western Australia
 t: +61 8 9254 6600
 admin@coastandports.com.au


m p rogers & associates pl
 coastal and port engineers

SCALE 1:2,500
AT A3

AUGUST 2021
 SK1905-01C

P:\MRA Paving Jobs\K1905 CONF Rowe - Onslow CHRMRA\5 MRA Drgs\Sketches\SK1905-01

Appendix B Coastal Inundation Hazard Map



AT CORRECT SCALE THIS IS 100 mm

AT CORRECT SCALE THIS IS 100 mm

NOTES:

1. AERIAL PHOTOGRAPH PROVIDED BY LANDGATE TAKEN IN FEBRUARY 2020.
2. INUNDATION LEVEL TAKEN FROM CARDNO (2016). INUNDATION LEVEL APPLIED USING MOST RECENT SURVEY OF THE AREA. (WATER CORPORATION 2005 & BENCHMARK SURVEYS 2021).
3. SITE PLAN PROVIDED BY MILIEU CREATIVE IN AUGUST 2021.

LEGEND:

- 2110 INUNDATION ALLOWANCE (4.55 mAHd)
- - - LOT 300 BOUNDARY

m p rogers & associates pl
coastal and port engineers

Suite 1, 128 Main Street
Osborne Park 6017
Western Australia
t: +61 8 9254 6600
admin@coastalports.com.au

DRAWN M. PETERSON
CHECKED M. ROGERS

COASTAL INUNDATION HAZARD ALLOWANCE
ONSLow TOWNSHIP VILLAGE

SCALE 1:2,500
AT A3

AUGUST 2021
SK1905-02C

P:\MRA Paving Jobs\K1905 CONF Rowe - Onslow CHRMRA\5 MRA Dwg\Sketches\SK1905-01

m p rogers & associates pl
www.coastsandports.com.au



ATTACHMENT 6

SERVICING REPORTS

Onslow Township Village

Engineering Servicing Report

Project No: 21-195

Table of Contents

1	Introduction	3
1.1	Report Qualifications	4
2	Site Conditions	5
2.1	Geology	5
2.2	Topography/Earthworks Concept	5
2.3	Groundwater Levels	5
2.4	Contamination.....	5
2.5	Bushfire Risk.....	6
3	Infrastructure	6
3.1	Stormwater Drainage	6
3.2	Wastewater Reticulation.....	6
3.3	Water Reticulation	7
3.4	Fire.....	7
3.5	Gas Supply	7
3.6	Electrical Supply.....	7
3.7	Communications	7
4	Conclusion	7

- Appendix One: Architectural Plan
- Appendix Two: Geological Series Map
- Appendix Three: Lidar Survey
- Appendix Four: Civil Concept Plan
- Appendix Five: Landscape Concept Plan
- Appendix Six: Modelled Catchments
- Appendix Seven: 1% AEP Inundation Extent
- Appendix Eight: Wastewater Plan

Revision	Description	Author	Date
0	Issued For Review	Andrew Tucker	05/08/2021
1	Issued For Review	Andrew Tucker	27/08/2021

1 Introduction

At the request of Milieu Creative, on behalf of the Mineral Resources Pty Ltd team lead by Rowe Group, Pritchard Francis have prepared this engineering servicing report to identify existing site conditions, existing services and potential upgrades required in order to facilitate the development of the Onslow Township Village.

The nominated development area, part of Lot 300 Back Beach Road, is located within the Shire of Ashburton, situated on the western side of the Onslow town centre. The proposed site is bordered by Lookout Point to the north, First Street to the east, Back Beach Road to the south and the Ian Blair Memorial Boardwalk/beach to the west. It is noted that part of the area facing Back Beach Road is being separated for potential use as a cultural centre.

Please refer to Appendix 1 for the Concept Plan prepared by Milieu Creative.



Figure 1 – 2020 Aerial photograph of Lot 300 Back Beach Road

1.1 Report Qualifications

In line with this report, Pritchard Francis make the following qualifications:

- This report was prepared exclusively for the Mineral Resources. Unless otherwise stated, the use of this report by third parties is not permitted.
- The information provided in this report may be considered valid for three (3) months from the date of the report.
- The information provided in this report is based upon the information and documentation provided by the consultant team and project architect. Pritchard Francis have relied on such information and documents. Where we are uninformed of developments outside of this report, Pritchard Francis cannot be held responsible or liable for any problems or issues that may arise as a consequence.
- Assumptions have been made which, if incorrect, have the potential to impact the recommendations of this report. Major development implications existing through avenues which cannot be assured at the time of this report, including the upgrading and provision of utility services, WAPC Conditions, DA Conditions, Local Authority Scheme Requirements, timing of adjacent developments, etc.
- Unless otherwise stated, the capacity of existing services has not been verified via engineering calculations. Where required, external consultants may need to be engaged to provide accurate assessments of existing and future servicing capacity.
- A site visit has not been conducted as part of this desktop study. An underground service scan has not been completed and information containing existing service information may differ from the physical service locations. Where possible, Pritchard Francis recommend verifying existing service locations and conditions.
- The civil designs presented in this report are conceptual in nature, and by no means depict the ultimate design solution. Detail design and documentation will be necessary to validate all design levels and gradients to ensure compliant with the client brief, Australian Standards, Austroads and relevant authority guidelines.

2 Site Conditions

2.1 Geology

The Australia 1:250,000 Geological Series map of Onslow (SF50-5) classifies the site as 'Qs: Beaches and coastal dunes – Light grey, unconsolidated and poorly consolidated quartzose calcarenite'.

The previously undertaken Golder Desktop Study indicates greenfill in the location of the proposed township. Proof rolling will be undertaken where possible. It is assumed that standard building footings for the area will be adequate after site preparation. Some infiltration is expected based on the geological series of the area.

Further geotechnical testing would be required to confirm site characteristics such as infiltration rate and site classification.

Please refer to Appendix 2 for the Geological Series Map of Onslow.

2.2 Topography/Earthworks Concept

The site generally falls from the north-east to the south-west, with levels undulating significantly within the bounds of the high points of approximately RL 17.0m and the low points of approximately RL 3.0m.

Pritchard Francis, in coordination with the Architect and Landscape Architect have implemented a design such that impact on existing topography is minimised in order to maintain the natural characteristics of the site. Natural contours and have been utilised in the development of the stormwater concept plan.

Limited site disturbance will be achieved by localising necessary changes to areas with key structures, access carpark and bus bay.

Review of the Lidar survey and concept plan indicate that earthworks (cut/fill) can be balanced on site, eliminating the need for import and/or export of fill.

The development will share a border with a proposed cultural centre to the south. The cultural centre will be bound by the Iron Ore township on the northern side, and Back Beach Road on the southern side. The access track shall double as a wellness track to achieve vehicle access for bushfire compliance purposes.

Please refer to Appendix 3 for the Lidar survey, Appendix 4 for the Pritchard Francis Earthworks, and Appendix 5 for the Landscape concept plan.

2.3 Groundwater Levels

It is not expected that groundwater levels will impact earthworks on site. Groundwater levels may impact the sewer discharge upgrade during construction and may need to be managed at such time.

2.4 Contamination

The Department of Water and Environmental Regulation contaminated site database indicates that no sites within the land development area are registered as contaminated sites. The publicly available database lists classified sites under the categories 'Remediated for restricted use', 'Contaminated – remediation required' and 'Contaminated – restricted use'.

DFES has placed the site under the UXO category 'Slight Potential', citing 'Anti-aircraft artillery live firing practices using high explosive ammunition during WWII. Aerial bombing also highly likely'.

The site is listed as not impacted by contamination according to Landgate.

2.5 Bushfire Risk

The Department of Fire and Emergency Services (DFES) bushfire risk mapping indicates that the site is within a bushfire prone area.

Reporting has been completed by Linfire, and the findings used as part of the overall submission.

Pritchard Francis has made provisions for relevant vehicle access requirements and duplicated the function as part of the perimeter wellness track under section *A3.5 Private driveway longer than 50 metres of SPP 3.7*.

3 Infrastructure

3.1 Stormwater Drainage

Stormwater is to be managed primarily via overland flow. The proposed development aims to minimise changes to the existing site and as such, overland flow paths have been chosen to utilise the existing depressions in the topography.

Based on the minimal disturbance intended, the catchment areas have not been changed despite the addition of impervious areas.

Please refer to Appendix Six for the Modelled Catchments and Appendix Seven for the 1% AEP Inundation Event plans.

All stormwater flows from vehicle access ways shall be captured and treated as part of the first flush. All other run-off from impervious areas within Catchment C will be directed via overland flow to Storage C for infiltration and discharge.

Minor event (20% AEP) and Major Event (1% AEP) events will be managed via overland flow to the existing natural depressions for storage and infiltration. Refer to the 1% AEP Inundation Event for storage locations.

The pods orientated around the main buildings will require confirmation of free drain discharge for 1% AEP events.

Please refer to the 360 Environmental Urban Water Management Plan Report for more information.

3.2 Wastewater Reticulation

The Water Corporation esinet data obtained on 20 July 2021 indicates there is wastewater servicing potential around the site. Wastewater services are viable from two locations near First St, on the eastern side of the site:

- Ø150mm at the intersection of First St and Third Avenue.
- Ø150mm on Simpson St, IL 0.93, near the intersection of First St and Simpson St.

Pritchard Francis believe the most efficient option to be the connection point within Simpson St. This location enables servicing of the main facility and pods with adequate cover and allows for a main sewer line. This will enable connection of the minor lines before discharging at Simpson St. This strategy compliments the natural topography and will minimise excavation.

Servicing of the internal sewer has been validated in accordance with AS3500 by Stantec to achieve gravity discharge.

Please refer to Appendix Eight for the Wastewater Plan.

Water Corporation has advised that it is expected to have treatment capacity for the increased demand (nominated above the likely ultimate use). Pritchard Francis are awaiting advice regarding potential need for in line upgrades to the McGrath Ave pump station and associated pressure main and whether this will be completed under headworks or customer funded works agreements.

3.3 Water Reticulation

The Water Corporation esinet data obtained on 20 July 2021 indicates that the development can be served by the following services;

- 250AC water reticulation main located within the 'Lookout Point' on the north-eastern boundary of the site.
- 150AC Water reticulation main in the Simpson Street road reserve, accessible from First St.

A concept plan based on utilisation of the Third Ave service. Connection to the site is expected to have a tank to buffer peak flows. Capacity of the service is to be coordinated with Water Corporation. The intent would be to disguise this in the landform or via screening.

3.4 Fire

Hardstand and fire appliance accessway shall be provided in accordance with the BCA and shall be designed and constructed in accordance with AS2419.1 and has been provided for.

3.5 Gas Supply

There is currently no available gas service in proximity to the site.

3.6 Electrical Supply

Pritchard Francis is awaiting confirmation of availability of electrical services from the electrical consultant. It is expected that capacity will need to be made available generation capacity and that of the existing network.

3.7 Communications

There is nearby Telstra cabling located in Simpson St and Third Ave on the eastern side of the development site.

NBN access mapping confirms the site is serviceable.

4 Conclusion




This report outlines the existing physical conditions and existing road/infrastructure capable of servicing the proposed development site. Pritchard Francis confirm that the site is accessible and can be served with roads, electrical, water, sewer, stormwater drainage and communications infrastructure.

Appendices

Appendix One:	Architectural Plan
Appendix Two:	Geological Series Map
Appendix Three:	Lidar Survey
Appendix Four:	Civil Concept Plan
Appendix Five:	Landscape Concept Plan
Appendix Six:	Modelled Catchments
Appendix Seven:	1% AEP Inundation Extent
Appendix Eight:	Wastewater Plan



Appendix One: Architectural Plan

Appendix Two: Geological Series Map



Appendix Three: Lidar Survey



PROJECT LOCATION PROJECT TYPE PROJECT SITE		 		PROJECT DATE: 19/07/2021 LOCATION: Onslow Lot 300 Survey Feature Survey	
RME GEORGE PI MARGARET PI		RME GEORGE PI MARGARET PI		PROJECT STATUS Information	
RME GEORGE PI MARGARET PI		RME GEORGE PI MARGARET PI		PROJECT ID BMS-MRL-D101-FS-DG-102	
RME GEORGE PI MARGARET PI		RME GEORGE PI MARGARET PI		REV 0	

Appendix Four: Civil Concept Plan

Appendix Five: Landscape Concept Plan



2.0 Landscape Plan

PROGRAM	
1	Bus Stand (Pickup/Dropoff)
2	Sheltered Community Playground
3	Dedicated Dropoff (Small Vehicles, Short Term)
4	Terraced Entry Plaza
5	Water Feature
6	Recreation Turf
7	Outdoor Gym
8	Cricket Net & Beach Volley Ball
9	Relax Zone (BBQ, Hammocks, Furniture, Shade Structure)
10	Mini Golf
11	Alfresco Deck With Terraced Embankment
11	Pedestrian / Maintenance Vehicle Access (with shade structures and comfort nodes)
12	Pedestrian Access (Boardwalk with shade structures and comfort nodes)
13	Security Fence
14	Entry Statement Wall


GENERAL	
	Site Boundary

SURFACES	
	Pedestrian Access Paving
	Plaza Paving
	Asphalt (Carpark)
	Asphalt (Maintenance Access)
	Composite Timber Boardwalk
	Fibre Reinforced Plastic Boardwalk
	Stabilised Gravel
	Pool

PLANTING	
	Lawn
	Native Dune Mix Planting - Managed Sparse
	Native Swale Mix - Managed Sparse
	Native Shrub Mix - Managed
	Proposed Native Tree

- Refer to Civil Engineers drawings for grading plan

Appendix Six: Modelled Catchments



Legend

- Survey Area Boundary
- Catchment A
- Catchment B
- Catchment C
- Sub Catchments**
- Access Track
- Building
- Oval
- Road
- Road A
- Road B
- Road C
- Swimming Pool

360 Environmental
 8/10 Bermansley St, West Leederville, 6007 WA
 (08) 9388 8360
 (08) 9391 2360
 www.360environmental.com.au

Scale: 1:3,500 @ A4
 Meters: 0, 40, 80, 120

LOCALITY MAP



PROJECT ID	DATE
4757	27/08/2021
HORIZONTAL DATUM AND PROJECTION	
GDA 1984 MGA Zone 50	
CREATED	CHECKED
LF	NC
APPROVED	REVISION
NC	0

Rowe Group c/o Mineral Resources Limited
 Lot 300 Back Beach Road, Onslow
 Urban Water Management Plan

Figure 7
 Modelled Catchments

Appendix Seven: 1% AEP Inundation Extent





Figure 9
 1% AEP Inundation Extent

COPYRIGHT: THIS DOCUMENT IS AND SHALL REMAIN THE PROPERTY OF 360 ENVIRONMENTAL. THIS DOCUMENT MAY ONLY BE USED FOR THE PURPOSE FOR WHICH IT WAS COMMISSIONED AND IN ACCORDANCE WITH THE TERMS OF ENGAGEMENT FOR THE COMMISSION. 360 ENVIRONMENTAL DOES NOT HOLD ANY RESPONSIBILITY FOR THE ABUSE OF THIS DOCUMENT.

Appendix Eight: Wastewater Plan



Title	SITE PLAN SEWER SERVICES
Client/Project	ROME GROUP ONSLOW TOWNSHIP VILLAGE
Project No.	301250498
Revision	C
Scale	1:1000
Drawing No.	HY-1-00

Client/Project Logo	
Copyright Reserved	All rights reserved. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without the prior written permission of Stantec Inc.

Issue Status	PRELIMINARY NOT FOR CONSTRUCTION This document is intended for the use of the architect for other purposes and not for construction.
Notes	

Revision	By: <u> </u> Date: <u> </u>
----------	--

Scale	1:1000
Drawing No.	HY-1-00

Onslow Township Village

Revision

Revision	Date	Comment	Prepared By	Approved By
001	26.07.2021	Draft Update Issue	ESV, ML, AD, SK	ESV
002	30.07.2021	Preliminary Issue for Review	ESV, ML, AD, SK	ESV
003	06.08.2021	Final Issue	ESV, ML, AD, SK	ESV
004	25.08.2021	Revised DA Updates	ESV, ML, AD, SK	ESV

1.	Introduction	1
2.	Project Overview	2
3.	Critical Issues	3
4.	Electrical Services	4
4.1	General Overview	4
4.2	Incoming Service Connections	4
4.3	Main Distribution and Site Wide Electrical Infrastructure	6
4.4	Buildings Works	8
5.	Fire Protection Services	10
5.1	Incoming Service Connection	10
5.2	Bushfire Advice	10
5.3	Design Standards	10
5.4	Design Criteria	11
5.5	Primary Fire Protection Spatial Requirements	12
6.	Hydraulic Services	13
6.1	Standards	13
6.2	Design Criteria	13
6.3	Fixtures & Taps	13
6.4	Sewer	14
6.5	Stormwater Collection	14
6.6	Trade Waste	15
6.7	Cold Water	15
6.8	Hot Water Services	17
6.9	LP Gas Services	18
7.	Mechanical Services	19
7.1	Design Standards	19
7.2	Design Criteria	20
7.3	Mechanical Services Scope	24
7.4	Mechanical Services Example Systems	26

Appendix A – Electrical Drawings

Appendix B - Hydraulic & Fire Drawings

Appendix C – Mechanical Drawings

1. Introduction

This Multi-Disciplinary Services Brief has been prepared at the request of Rowe Group for the development of the Onslow Township Village in Onslow, WA. It has been prepared in order to outline our understanding of the Electrical, Fire Protection, Hydraulic and Mechanical services Works and to support the servicing strategy for the project's Development Application process.

This document services as a benchmark which our services much achieve. We request that you read this carefully so that you have a clear understanding of the scope of our works.

We would welcome any comments or queries you may have on the information provided in this Brief.

This Brief has been prepared based on the following information:

- Thalanyji Presentation Package by Milieu Creative
- Functional Brief Revision 1 incorporating MRL Comments
- Drone images and videos of the proposed development site
- OIP-0000-GE-SOW-0001 – Onslow Iron Project Facilities Requirements dated 12th February 2021
- Project kick of meeting held at Rowe Group on the 7th July 2021
- Architectural Drawings by Milieu Creative on the 20th August 2021

2. Project Overview

The Onslow Township Village, located at Lot 300 in Onslow WA, will be the permanent village style accommodation facility and will be designed and built as long-term accommodation and facilities to cater for the mine operations workforce.

The Village will be designed to support up to 500 rooms including central facilities and utilities and incorporate the following major elements:

- Accommodation Pods
- Laundry / Field Storage
- Restaurant
- Tavern
- Administration
- Induction & Training Rooms
- Lockers & Creche
- Medical Centre
- Gate House
- Storage Sheds
- Gymnasium
- Wellness Spaces
- Swimming Facility
- Multi-Purpose Sports Courts
- Indoor and Outdoor Cricket
- Golf Facilities
- Recreation & Common Rooms
- Carparks
- Service Compounds

3. Critical Issues

The following list itemises the critical issues for the project's building services:

- Redundancy of services (no single point of failure)
- Ease of maintenance
- Systems design being cognisant of site location being within a cyclonic region (i.e. floor mounted plant/equipment)
- Coordination of site infrastructure to achieve functionality at a reasonable level of cost
- To provide a design that minimises initial capital cost without excessively compromising quality or ongoing maintenance costs.
- To provide adequately sized plant/infrastructure services that allows an acceptable level of flexibility for future development/redevelopment.
- Operational requirements of the Cyclone Shelter

4. Electrical Services

4.1 General Overview

The Electrical Services encompasses the following key subsystems:

- Electrical power distribution from utility (Horizon Power interface) to final outlet or fitting.
- Reticulation of structured communications cabling (Fibre and copper) from Retail Service Provider (RSP) termination point to end distribution outlet or rack.
- Provision of internal and external lighting services.
- Allocation in conjunction with client requirements for electronic access control and camera surveillance systems.

The Electrical Services shall be designed to comply with current National Construction Codes (Building Code of Australia), Safety in Design requirements, Worksafe Regulations, WA Electrical Requirements and the following Standards and Codes amongst others:

- AS/NZS 1670 Fire detection, warning, control and intercom systems - System design, installation and commissioning
- AS/NZS 1680 Interior and Workplace lighting (all parts)
- AS/NZS 1768 Lightning Protection
- AS/NZS 2293 Emergency escape lighting and exit signs for buildings
- AS/NZS 3000 Wiring Rules
- AS/NZS 3008.1 Electrical Installations - Selection of Cables - Cables for Alternating Voltages Up to and Including 0.6/1 kV - Typical Australian Installation Conditions
- AS/NZS 3084 Telecommunications Installations, Telecommunications Pathways and Spaces
- AS/NZS 61439 Low Voltage Switchgear and Control Assemblies
- AS/NZS 11801 Information Technology - Generic Cabling for Customer Premises (series)
- AS 4806.1 Closed Circuit Television (CCTV) – Management and Operation
- AS/NZS 61000 Electromagnetic compatibility (EMC)

(in the case of discrepancies with user requirements) is to be advised as the design of the building is progressed.

4.2 Incoming Service Connections

4.2.1 Power

The preliminary maximum demand for the site has been calculated to be 941 kVA. This would require a provision of a 1MVA utility connected substation. Given the anticipated long runs of low voltage submain cables, Stantec proposes that a sole use substation be sought to be located centrally to the site.

The requirements around a sole use substation will require provision of the following:

- Horizon Power High Voltage (HV) Ring Main Unit (RMU) on site boundary.
- Horizon Power underground HV cable along entry road.
- Horizon Power owned and maintained sole-use substation including 1 MVA transformer located central to main facilities area.

Sole-use substations are only approved on request, so subsequent development approval an application for the feasibility of this proposal is to be sought with Horizon Power.

A preliminary layout and nominal locations have been shown on the masterplan appended to this report to allow for the provision of space.

The ability for the Horizon Power distribution network to deliver the required power to the site is yet to be confirmed but recent town upgrades including inclusion of renewable energy sources suggest there is capacity available.

On sites with a very long cable runs an assessment of the suitability of a high voltage connection could be considered. Initial recommendation is that long term maintenance and operations would make an exclusively low voltage distribution system more suitable for this application.

The above is provided for concept information as it is understood that MRL will manage the site power supply and engagement with the authority for the final details around there assets. It has been confirmed that MRL will manage the liaison, approvals and commercial negotiations with Horizon Power or the chosen electrical distributor.

4.2.2 Telecommunications Lead-In

This development is within an area shown has being 'ready to connect' to a NBN service. However, this service is not shown to be a wired solution and is detailed as a 'NBN Satellite' service.

The previous engineering services report dated 2012 indicates there is a legacy pit and pipe network throughout the town for copper services, as well as recent town subdivisions appear to have been serviced with pit and pipe for Telstra connection.

Provision for a Fibre-ready connection to the main communications room will be made as is required for all new developments. This provision references dedicated ducts pits and power provisions for utility services in this space. Unlike power, the connection of a communications utility required engagement from the end-client through the appropriate services provider, likely Telstra in this case.

Advice from the client in conjunction with their communications providers will indicate any additional pipe, ducts that need to be allocated for site connectivity.

4.3 Main Distribution and Site Wide Electrical Infrastructure

4.3.1 Power

Preliminary allocation of electrical distribution board infrastructure has been considered with respect to submain cable lengths and feasibility of a centrally located sole-use substation.

Refer to appendix for the power distribution plan for the site.

The following provisions for electrical distribution boards has been identified and will form the primary power distribution for the facility:

- Site Main Switchboard (SMSB) – Contiguous to Substation and will be primary distribution node for all buildings.
- Accommodation Unit Neighbourhood Main Distribution Boards (MDB) 1, 2, 3 & 4 – Each board to support in order of 125 Accommodation units as well as common lighting and power services through neighbourhood areas.
- Administration Building MDB
- EOT and Medical MDB
- Training Distribution Board (DB)
- Restaurant MDB
- Tavern MDB
- Restaurant DB 1, 2 & 3
- Gymnasium MDB
- Multipurpose Court DB
- Pool and Oval site DB
- Gatehouse DB
- Stores and Maintenance DB
- Accommodation Unit Load Centre (1 -500)

Mechanical Services switchboard (MSSBs), sewer pump station (SPS) control panels, motor control centres (MCCs) are all electrical switchboards provided by the vendor or engineering service responsible for their design and construction.

Additional switchboards for interfaces with solar and diesel generation systems may be required as design development. Equally additional electrical distribution infrastructure may be added following detailed load and cable sizing calculations that will enable the technical and cost factors to be considered appropriately.

4.3.2 Metering

Provision of a single supply authority meter is recommended at the site main switchboard and the use of appropriately rated and certified billing meters be provided for the central facilities, should future leasing be incorporated.

Final alignment with sustainability initiatives will required a networked metering system to be deployed with energy meters allocated through MDB, DB's and other electrical control panels and plant.

4.3.3 Power Generation

Provision for connection of diesel generator is to be allocations at the customer-owned Site Main Switchboard. This allocation of a permanent 600-800 kW generator should only be made on a provisional basis until confirmation of the following items can be resolved:

- Horizon Power Onslow Town distribution grid capacity.
- Allocation of safety services from an engineering system design perspective.
- Allocation of requirements for back-up around the cyclone shelter.

4.3.4 Structured Cabling Distribution – Communications

The allocation of space currently indicated within the EOT, Lockers and Medical building as defined by the project brief is suitable for the main incoming interface point as well primary communications racks and distribution nodes. IT services and active equipment will also be stored within this space. The current assumption is that the end-client or operator will provide all active equipment (servers, computers, switches, routers/modems, wireless access points etc.) throughout the facility.

Given the current requirement in the project brief for internet/data based services within each accommodation unit; Stantec's recommendation is that fibre optic services be provided to each accommodation unit. This is provided over a network known as a GPON network. This active network design scope and delivery will need to be resolved through the next design phase. This network will enable the site to utilise a converged network with security, entertainment and data/internet services to share the same physical cabling. ***This approach is one a few for camp/villages of this nature, the client may have prior experience that informs a preference for this type of a solution and as such a review on this item and direction is requested prior to initiation of detailed structured cabling design activities.***

Under the solution above a multi-core fibre optic cables will be distributed from the main communications to laundry facilities then onto each accommodation unit. As such, each laundry unit will require a communications room as detailed below:




Figure 1: Laundry Communications Room - Space Planning

4.3.5 External Lighting

External carpark lighting will be designed in accordance with AS/NZS 1158, be controlled through the utilisation of time clock and photo-electric sensors.

External car park lighting depending on council and end-user requirements can often be switched off between at night time to reduce the risks surround obtrusive light to surrounding residents. Typically this would be between the hours of 11pm and 2am, although normally adjustable based on client preferences, pending council advice.

4.3.6 Site Electronic Access Control and CCTV System

The site is currently provisioned with a gatehouse and current design assumes the use of a electronic access card for vehicle access and provision of VOIP-based intercom system for time this gatehouse is unattended. Other external non-accessible areas may utilize similar systems as well as access control plant rooms and pedestrian gates. Physical security elements are not part of the electrical services package.


In conjunction with the external electronica access control points a site wide CCTV system is anticipated for all entry and exit points to buildings and main site entry points. In addition, CCTV coverage throughout common areas and main thoroughfares of accommodation unit neighborhoods is also to be provisioned.


4.4 Buildings Works

4.4.1 Accommodation Units

Internal fit-out of the accommodation units is understood to be aligned with the procurement of modular unit. Irrespective interior requirement will developed further in future design stages.

Pertinent to initial space planning is the allocation of distribution board and GPON network Optical Network Termination Device (ONT). Please find typical arrangement below:





ELEVATION, SECTOIN AND IMAGE OF INTERNAL DB AND ONT ARRANGMENT

Figure 2: Internal & External DB/ONT Arrangements

4.4.2 Central Buildings

The small power, communications, lighting and security provisions for these buildings will be developed in conjunction with the functional requirements, client briefings as well as BCA and Australian Standards as the project progresses.

5. Fire Protection Services

5.1 Incoming Service Connection

The fire protection services design assumes that the incoming mains will be capable of supplying the required flow rate for the fire hydrant system (20 L/s) at a residual pressure of at least 200 kPa.

Flow testing is yet to be carried out in the street mains and at this stage we are unable to determine the available inflow to the site. We recommend that this is undertaken as early as practicable during the design. At this stage we are assuming that we are required to provide full storage to the development, with an additional tank suction line required to provide water to the attending fire brigade.

5.2 Bushfire Advice

The following advice has been provided by the project Bushfire Consultant

- Recommend we allow 50kL additional firewater for bushfire fighting purposes, with a minimum onsite firewater storage of 200kL
- The standard booster and hardstand arrangements should be sufficient.
- There are existing street hydrants nearby but unsure of what flow and pressure these have.

5.3 Design Standards

- Fire services to comply with the National Construction Code of Australia 2019.1
- Fire services to comply with all current statutory requirements and guidelines
- Fire Services to comply with current Australian Standards where applicable and particularly the following:

Standard	Year	Name	
AS 1851	2012	Routine Service of Fire Protection Systems and Equipment	
AS 2419.1	2005	Fire Hydrant Installations	Part 1: System Design Installation and Commissioning
AS 2441	2005	Installation of Fire Hose Reels	
AS 2941	2013	Fixed Fire Protection Installations – Pump Set Systems	
AS 3500.1	2003	Plumbing and Drainage	Part 1: Water Services

5.4 Design Criteria

5.4.1 Fire Hydrant System

Fire hydrant protection is provided for the non-accommodation buildings only exceeding 500m² fire compartment floor area.

The fire hydrant system is to be designed based on the following:

- Number of operating hydrants 2 outlets
- Minimum flow rate – pumped 5 L / s each
- Minimum residual pressure 700 kPa
- Minimum flow rate – boosted 10 L / s each
- Water Storage 2 x Cylindrical Tanks 7.768 m diameter x 3.6 m high each
Minimum effective capacity 144 kL

5.4.2 Fire Hose Reels

Fire hose reels are to be designed based on the following, supplied from the fire hydrant system:

- Protected areas all areas as outlined in BCA advice
- Nominal Hose Diameter 19 mm / 25 mm
- Minimum flow rate 0.33 L / s each / 0.41 L/s each
- Minimum residual pressure 220 kPa
- Number of operating hose reels 2 most hydraulically disadvantaged

5.4.3 Portable Fire Extinguishers

Portable fire extinguishers are to be provided based on the following:

- Protected areas Areas nominated in BCA Table E1.6 only
- Design Standard Primary Protection
- Additional Requirements Extinguishers provided to suit Fire Engineering requirements

5.5 Primary Fire Protection Spatial Requirements

Outlined below, and in associated mark-up drawings are the key spatial requirements for the fire protection services:

Item	Location	Size	Comments
Fire Booster Cabinet	Adjacent Main Street Entrance	3000 (w) x 800 (d) x 1800 (h)	Location to be confirmed with Fire Brigade. Can be free-standing withing sight of main site entry but no less than 10m from the building unless additional fire rating is provided to building external wall.
Fire Pump Room	Adjacent Fire Tanks	6000 (w) x 6500 (d) x 2400 (h)	Location requires direct Fire Brigade access, or alternative solution required. Preferably located with good access to roadways/pathways.
Fire Water Tanks	Adjacent Pump Room	7768Ø x 3600 (h)	Tank requires minimum 600 mm clearance all sides.
Fire Indicator Panel	Internal wall inside main building entry	700 (w) x 350 (d) x 2100 (h)	Location to be confirmed with Fire Brigade.

6. Hydraulic Services

6.1 Standards

- Hydraulic services to comply with the National Construction Code of Australia 2019.1.
- Hydraulic services to comply with all current statutory requirements and guidelines including the Shire of Ashburton, Water Corporation of Western Australia, Department of Fire and Emergency Services, Department of Health and the Department of Environmental Protection.
- Hydraulic Services to comply with current Australian Standards where applicable and particularly the following:

AS 3500	:	National Plumbing and Drainage Code incorporating:
Part 1	:	Water Supply
Part 2	:	Sanitary Plumbing and Drainage
Part 4	:	Heated Water Services
AS 2419	:	Fire Hydrant Installations
AS 2441	:	Fire Hose Reel Installations
AS 5601	:	Gas Installations

6.2 Design Criteria

- Hot Water

:	Storage Temperature (domestic use) minimum 60°C
:	Supply Temperature (commercial use) minimum 65°C
:	Supply Temperature (domestic use) maximum 50°C
:	Supply Temperature to disabled facilities maximum 45°C

- Stormwater:

We note that it is not expected to provide rainwater catchment roof gutters in this region due to rainfall intensities and cyclone wind region requirements. We are not proposing to provide roof rainwater downpipes and are proceeding on the basis that the roof edges will be designed to allow rainwater to cascade on to hardstand or appropriately managed surfaces.

6.3 Fixtures & Taps

- Provision for first grade commercial quality sanitary fixtures, fittings, and tapware are to be made for the development.
- Provision of fixtures and tapware conforming to the WELS (Water Efficiency Labelling Standards) which identifies the following maximum flow rates. Further to this, we expect that additional reductions in flow rates are to be proposed by the sustainability consultants for the project.

-	Showers	@	9 L/min
-	Hand Basins	@	6 L/min
-	Sinks	@	6 L/min
-	Toilets	@	Dual Flush 4.5/3 L

Nomination of sanitary fixtures and tapware will be determined in consultation with the architect for client sign off during the project detailed design.

6.4 Sewer

A conceptual sewer layout has been provided to the project Civil Engineer for inclusion into the site Authority mains extensions required to service the project.

With circa 500 Pods including a bathroom, kitchenette and laundry of 14FU's, the development is expected to service around 7,150FU for sewer. While the below layout is achievable, there is a possibility that site levels may require the installation of pump stations to achieve sewer falls. These are to be avoided where possible to reduce ongoing maintenance of mechanical pumps and control panels.




Figure 3: Conceptual Sewer Layout

6.5 Stormwater Collection

- No provision will be made for eaves and box gutters, gutter sumps, overflows, expansion joints and downpipes.
- We note that due to cyclonic conditions in the region the common design practice for roof drainage is not to provide guttering and associated downpipes. Typically, roofs drain onto graded concrete pathways or designed swales to avoid soil erosion whilst still dispersing roof water flow. In our experience, the primary reasons for not providing roof stormwater collection systems are:
 - Due to rainfall intensities experienced in the region, gutter and downpipe sizing is excessive.
 - The excessive sizing of gutters exacerbates the issue of appropriately fixing guttering to roof structures to withstand cyclonic winds.

6.6 Trade Waste

6.6.1 Kitchen/Greasy Waste

- Provision for the collection of all grease waste from kitchen cooking and food preparation areas via fixture wastes from food preparation sinks, hand wash basins, bain maries, cool room/freezer washdown and condensate waste drains, bucket traps and industrial floor wastes discharging to a suitably sized filtered grease arrestor

Note: Fixture wastes from glass washers, dishwashers and pre-rinse sinks will discharge directly to the domestic sanitary drainage system so that excessive and high temperature wastewater discharges bypass the grease trap

- Provision for a 15mm hose connection tap located within 6m of the grease arrestor to assist maintenance cleaning and complete with required backflow prevention device
- Provision for a 240 V, 10 A, 3 pin weatherproof GPO to be located within 2m of the grease arrestor industrial waste sampling point to assist the Authorities use of sample and monitoring process equipment
- Provision for independent venting to atmosphere of grease arrestor

6.6.2 Medical Waste

- A dilution chamber may be required for the medical clinic dependent on the testing and materials used on site.
- An application to discharge form will need to be completed to ensure that appropriate pre-treatment devices are installed prior to connection to the sewer network.
- Typically, we expect the requirement of a small below ground dilution chamber adjacent the medical clinic.

6.6.3 Commercial Laundry Operations

- Laundry pods for commercial uses (i.e. linens and heavy washing) may require lint/cooling pits prior to discharge into the site sewer network.
- Provision for the collection of all commercial laundry discharges to a suitably sized lint/cooling pit.
- Provision for a 15mm hose connection tap located within 6m of the lint trap to assist maintenance cleaning and complete with required backflow prevention device
- Provision for a 240 V, 10 A, 3 pin weatherproof GPO to be located within 2m of the lint trap industrial waste sampling point to assist the Authorities use of sample and monitoring process equipment
- Provision for independent venting to atmosphere of lint trap/cooling pit.

6.7 Cold Water

Water is available to the development via the 200AC Water Corporation water main in Third Avenue. We understand discussions with this Authority are ongoing to determine the location and availability of water take off.

- Provision for reticulated cold water supplies to all sanitary fixtures, fittings and tapware as required incorporating all required maintenance isolation valves throughout the development, with a large cold water ring main providing redundancy and continuity of pressure availability.

6.7.1 Potable Water Storage

As outlined in the *Onslow Iron Project – Facilities Requirements* section on water treatment plant, the site requirements allow for 250L/person/day. While this is typical for mining camps, this allowance on a per person basis will also cover for additional usage at the central facilities of the development. We also understand that it may only be a 6-12 month period where the camp is fully occupied, and that during general operations the development will operate at a lesser capacity. The difference between these scenarios is presented in the table below.

Water storage services have been sized to minimise the main incoming water service connection size to the Authority infrastructure, and to allow a 6-hour refill of half a day of water storage outside of peak demand times. This allows a morning showering peak to be refilled with 50% of the days potable capacity available for other uses.

Table 1: Site Water Demands

	Site Full Capacity	Site General Capacity
People	500	300
Daily Potable Water Use	250L/person/day	250L/person/day
Storage Tank Capacity	125kL	75kL
Site Potable Water Connection (6 hr 50% tank refill)	50mm @ 230L/min 208 L/min (3.47L/s)	40mm @ 120L/min 104 L/min (1.74L/s)
Monthly Potable Water Use	3,802 kL/month	2,281 kL/month
Annual Potable Use	45.625 ML/annum	27.281 ML/annum

Note: Demands reflect potable use only and excludes irrigation demand.



Figure 4: Conceptual Water/Fire Layout

6.8 Hot Water Services

Whilst recognising there is to be no or minimal gas supply to the site available to heat potable water, our design intent is to deliver the most energy efficient hot water generation system.

To this end, our design solution involves the use of heat pump technology for all hot water plant, with small local hot water demands possibly being met with the use of local electric storage units.

Further, we have conducted some preliminary investigations into solar contribution to hot water generation. Given the location of the site (being in a cyclonic region) we consider that, due to the extra requirements for structural robustness of the solar panel array support system, this may prove to be cost prohibitive. Further, initial investigations have revealed that a large "solar field" area would be required, which would be best placed to be utilized for solar PV electricity rather than hot water generation.

Given the above, we have not considered solar to be a viable alternative, particularly given the inherent energy efficiencies associated with the proposed heat pump units.

Table 2: Hot Water Supply Matrix

Area Served	Design Assumptions		Hot Water Plant
	Peak Demand	Hot Water Usage	
Pod Option 1 One Unit/2 Pods	Max two showers in operation at the same time	Average shower of 5-7 minutes per person at same time	Residential style heat pump, 200L capacity serving two pods.
Pod Option 2 One Unit/4 Pods	Max 3/4 showers in operation at the same time	Average shower of 5-7 minutes per person at same time	Residential style heat pump, 300/340L capacity serving four pods
Laundry Pods		Heavy Dirt Personable item washing	Commercial heat pumps with storage tanks to final demand requirements
Central Facilities Buildings			
Administration	Tea prep use or amenities only	-	Allow electric instantaneous hot water unit at point of use.
Medical Centre	Individual sinks/basin and amenities use	-	Allow electric instantaneous hot water unit at point of use.
Restaurant	Kitchen equipment to prepare meals for breakfast and dinner for 300-500 people	Allow 4L hot water per meal prepared. 2,000L per peak.	Commercial heat pumps with storage tanks. Gas backup optional if gas is considered for kitchen use. Each system manifolded to enable independent isolation of equipment to ensure no single point of failure. Electric or Gas water boost heaters in series for high temperature boosting if required.

Area Served	Design Assumptions		Hot Water Plant
Tavern	Kitchen equipment to prepare basic 'tavern' meals for 100 people + Alfresco	Allow 4L hot water per meal prepared. 600L per peak.	Commercial heat pumps with storage tanks. Gas backup optional if gas is considered for kitchen use. Each system manifolded to enable independent isolation of equipment to ensure no single point of failure. Electric or Gas water boost heaters in series for high temperature boosting if required.
Laundry		Linens	Commercial heat pumps with storage tanks to final demand requirements
Stores/Maintenance	Individual sinks/basin and amenities use	-	Allow electric instantaneous hot water unit at point of use.
Gymnasium/Wellness	Assume 44 people showering (2 football teams) over a period of 30 minutes	Assume an average shower length of 3 minutes per person	Commercial heat pumps with storage tanks. Each system manifolded to enable independent isolation of equipment to ensure no single point of failure. T
Recreation Room	Tea prep use or amenities only	-	Allow electric instantaneous hot water unit at point of use.

Note: Commercial Heat pumps are controlled by single electronic control module that is effectively a single point of failure for the system. Typically, a redundant module would be stored on site for changeover in the event of a failure in order to provide redundancy.

(Failure of this component would result in a short down time of the hot water system).

The Hot Water Supply Matrix sets out the hot water demand and equipment provisions for each building requiring hot water within the development as individual buildings with separate hot water plants.

6.9 LP Gas Services

With no reticulated gas available to the development, LPG is an option for providing a gas supply to the kitchen. LPG is available in Onslow and can be set up with a bulk cylinder or through a gas tank manifold.

We look forward to internal kitchen advice to provide additional options.

7. Mechanical Services

7.1 Design Standards

7.1.1 Statutory Design Standards

The National Construction Code (NCC) 2019 and, in particular, the “deemed to satisfy” conditions of:

- NCC 2019 Section J3.5 “Building Sealing - Exhaust Fans”
- NCC 2019 Section F4.5 “Ventilation of rooms”
- NCC 2019 Section J5 “Air Conditioning and Ventilation Systems”
- NCC 2019 Specification J5.2 “Ductwork Insulation and Sealing”

Australian Standards as follows:

- AS 1530 Methods for fire tests on building materials, components and structures
- AS 1668.1 The use of mechanical Ventilation and Air Conditioning in buildings -Fire and Smoke control in multi-compartment buildings
- AS 1668.2 The use of mechanical Ventilation and Air Conditioning in buildings - Mechanical Ventilation in buildings
- AS 5149 Refrigerating Systems
- AS 1682 Fire Dampers
- AS 1851 Maintenance of Fire Protection Systems
- AS 3000 SAA Wiring Rules
- AS 3666.1&2 Air Handling and Water Systems of Buildings – Microbial Control
- AS 4254.1 Flexible Ductwork – Fire resistance & Sealing only
- AS 4254.2 Solid Ductwork – Fire resistance & Sealing only

Client to advise requirements and guidelines including SHIRE / CITY COUNCIL (listed on DA Approval), Fire and Emergency Services Authority, Health Department and Department of Environmental Protection.

7.1.2 Safety in Design - Design Standards

These standards may be referenced in Safety in Design reports, compliance with these standards will be used to mitigate the relevant Health and Safety Risks.

Australian Standards as follows:

- AS 1668.1 The use of mechanical Ventilation and Air Conditioning in buildings -Fire and Smoke control in multi-compartment buildings
- AS 1668.2 The use of mechanical Ventilation and Air Conditioning in buildings - Mechanical Ventilation in buildings
- AS 1677 Refrigerating Systems
- AS 3000 SAA Wiring Rules
- AS 3666.1&2 Air Handling and Water Systems of Buildings – Microbial Control
- AS 2865 Confined Spaces HB213 Guidelines for Working in Confined Space

- AS 2896 Medical Gas Systems
- AS 2568 Medical Gasses – Purity of Compressed Breathing Air
- AS 1894 Storage and Handling of Non-Flammable Cryogenic and Refrigerated Liquids
- AS 1940 Storage and Handling of Flammable Combustible Liquids
- AS 5601 Gas Installations
- AS 3500 Plumbing & Drainage Codes
- AS 1228 Pressure Equipment - Boilers
- AS 2593 Boilers – Safety Management & Supervision Systems
- AS 1271 Safety Valves

7.1.3 Best Practice Design Standards

These standards will be followed where practical, Client to advise any standards which must be followed.

Australian Standards as follows:

- AS 1324 Air Filters for use in air conditioning and general ventilation
- AS 2107 Acoustics
- AS 3013 Electrical installations, wiring systems for specific applications
- AS 4254.1 Flexible Ductwork
- AS 4254.2 Solid Ductwork

7.2 Design Criteria

Air conditioning systems shall be designed to meet the following design criteria during normal operation with due allowance for solar loads, transmission loads, internal loads, occupancy level and infiltration loads.

All cooling and heating loads may incorporate a design/safety factor of 10%, which is to be added to the calculation of cooling and heating loads.

The design criteria proposed for the mechanical services will be based on the following parameters:

7.2.1 Design Temperatures

Max recorded ambient conditions - (Based on client brief)

Summer (maximum)	49.2°C DB 53%RH (assumed that RH recorded at 3pm Feb is coincident with Max daily temp)
Winter (minimum)	3.5°C DB

Mean ambient conditions – (Based on Bureau of Meteorology data)

Summer (maximum)	36.5°C DB 53%RH (assumed that RH recorded at 3pm Feb is coincident with Mean Max daily temp)
Winter (minimum)	13.1°C DB

Ambient conditions – (Based on AIRAH Weather data set for Comfort Conditions)

Summer (maximum)	36.5°C DB 53%RH (assumed that RH recorded at 3pm Feb is coincident with Mean Max daily temp)
Winter (minimum)	13.1°C DB

Internal Environmental Conditions

Air Conditioned Areas Only

Cooling	:	Nominal 24°C Dry Bulb
	:	40 - 60% relative humidity anticipated by virtue of cooling coil performance
Heating	:	21°C Dry Bulb
Control Tolerance	:	Plus or minus 1.5°C at the point of control for heating and cooling.
Humidity Tolerance	:	40-60% anticipated by virtue of cooling coil performance No specific humidity control provided.

Client to confirm internal design conditions

Evaporative Cooling

It is understood that evaporative cooling is to be avoided due to climatic location and relatively high ambient humidity levels during periods of the year.

7.2.2 Zone Sizes

Accommodation Rooms

Each room shall be treated as an independent zone capable of controlling the temperature in the space independent of the operation of other rooms.

Office Areas

Internal Zones	125m ²
Perimeter Zones	80m ²

Each office area shall be treated as an independent zone capable of controlling the temperature in the space independent of the operation of other zones. The above zone sizes are based on A-grade commercial office guidelines and will be used as a guide where practical.

Client to confirm zoning provisions.

Other Areas

Perimeter and internal zones within the air conditioned areas shall be capable of controlling the temperature independently.

7.2.3 Internal Loads

Accommodation

Occupancy	As per architectural drawings. (Typically 1 person per room).
Lights	10W/m ²
Equipment	25W/m ²

Office Areas

Office occupancy	10m ² /person
Lobby occupancy	5m ² /person
Lights	10W/m ²
Equipment	25W/m ²

Food & Beverage

Occupancy:	Dining area	1.5m ² /person
	Kitchen area	3.5m ² /person
Lights		10W/m ²
Equipment		5W/m ²

Gym & Recreation

Occupancy:	<i>Client to confirm</i>
Lights	10W/m ²
Equipment	<i>Subject to further client clarifications</i>

Cyclone Shelter (Restaurant area)

Occupancy:	<i>500 people – Client to confirm</i>
------------	--

7.2.4 Outside Air Flow Rates

Accommodation

All Areas	Natural ventilation. Compliance to be confirmed by Architect/Building Certifier
-----------	---

Office Areas

General	7.5l/s/person (based on high efficiency filtration)
---------	---

Food & Beverage

General	7.5l/s/person (based on high efficiency filtration)
Makeup air	Via pre-treatment air conditioning systems

Gym & Recreation

General	7.5l/s/person (based on high efficiency filtration)
---------	---

7.2.5 Exhaust Air Rates

Accommodation

Room Ensuite Exhaust 40l/s minimum

Common Laundry 10l/s/m²

Other

Toilet exhaust 10l/s/m²

Locker Rooms 5l/s/m²

Cleaners Rooms 10l/s/m²

Substation To meet Western Power requirements

Switchroom To meet Electrical Consultants requirements

Kitchen Exhaust to AS 1668.2

Simple Café (No cooking) Kitchen exhaust system not required

Simple Café (Cooking) 10l/s/m²

Restaurant Cooking Dedicated commercial kitchen exhaust system to AS 1668.2

Photocopying areas 10 l/s/m² (minimum)

Sick rooms 15-20 Ach/hr

Café kitchen hood In compliance with AS 1668.2 to be confirmed by Architect/Client

General ventilation Materials tech workshops, excluding technology process equipment, by Specialist.

7.2.6 Acoustic Criteria

The following criteria is indicative and subject to Acoustic Consultant review (ongoing).

Living areas 30-40 dB(A)

Sleeping areas 30-35 dB(A)

Work areas 35-40 dB(A)

Common areas 40-45 dB(A)

Restaurant 45-50 dB (A)

Toilets 50-55 dB (A)

7.2.7 Glazing and Building Fabric

Architect to advise building fabric.

7.3 Mechanical Services Scope

7.3.1 Air Conditioning

Air conditioning will be provided to all occupied areas. The method of delivery will be dependent on the type and size of the space. Broadly the systems fall into the following categories;

- High Occupancy / High Capacity Areas
- Large Office and Common Areas
- Accommodation and Small Standalone Areas

High Occupancy / High Capacity Areas

This includes areas such as the Restaurant, Tavern, Gymnasium and Recreation Buildings subject to further clarification of occupancy and room loads.

These areas will require large capacity systems and high outside air loads. To manage these requirements it is recommended that central packaged units be used for each space to reduce overall plant size and complexity.

This type of equipment is typically located on the roof directly above the areas served, although in this application it is recommended that the equipment be located at ground level to remove roof access maintenance and provide better protection from cyclone events.

Large Office and Common Areas

These spaces are proposed to be catered for using conventional split systems but utilising central outdoor equipment connected to multiple indoor units.

This will minimise the number of outdoor units whilst still providing individual temperature control to the required spaces within the building.

The indoor fan coil units are proposed to be fully ducted systems to enable flexible fitout and future reconfiguration.

Accommodation and Small Standalone Areas

Given the relatively small spaces associated with the accommodation rooms and the likelihood of these highly repetitive structures being modular, we recommend standalone split systems for each room.

These systems are proposed to utilise wall mounted indoor fan coil units to mitigate costs, both upfront capital and replacement cost at end of life.

Given that the accommodation areas are expected to remain unchanged, the limited flexibility of wall mounted units is not considered to be an issue for this project.

7.3.2 Ventilation

Ventilation systems will be provided to address code compliance. This will include:

- Dedicated ventilation fan to each accommodation room ensuite
- Central ventilation system to large toilet blocks within each building where applicable
- Specific minor systems to storage rooms and the like (dangerous goods consultant input will be required for areas where chemicals or the like are being stored)
- General ventilation to services rooms such as pump rooms, switch rooms, etc.
- Commercial kitchen exhaust systems to kitchen areas associated with the Tavern and Restaurant including commercial kitchen hoods and associated make up air supply

7.3.3 Refrigeration

Cool rooms and freezer rooms will be conditioned by dedicated refrigeration systems. All connected through a central monitoring system to track room conditions and alarm if room conditions drift from setpoints.

Indoor units are physically mounted within the rooms, whilst the outdoor units should be located externally but within screen plant areas to protect from cyclone events

7.3.4 Cyclone Shelter

Cyclone shelter accommodation needs to be suitably constructed to withstand the required storm events. This needs to be addressed by the Structural consultant and the Architect.

From a mechanical services perspective, the shelter must also include sufficient means for ventilation to ensure occupancy is not compromised for the potentially long periods associated with sheltering from a major cyclone event.

The recommended approach is to include manually operated ventilation openings to all sides of the shelter structure. This will enable occupants to configure the openings as and when required to best mitigate the impact of the external winds whilst ensuring the internal space remains well ventilation.

7.3.5 Local Climate

The local climate for Onslow is subject to high humidity for periods throughout the year. High humidity can result in condensation issues if due consideration is not given to thermal insulation and moisture barriers.

The incorporation of moisture barriers forms part of the building construction and is understood to be part of the architectural documentation.




The mechanical services will include all necessary insulation to prevent cold bridging due to humid air contacting cold surfaces of the mechanical services equipment. Where this is not possible, such as at valve or drain connections, appropriate condensate trays and/or drains will be provided.




In addition to protecting cold surfaces and moisture infiltration through the building fabric, infiltration through building openings must also be managed. For all large spaces (i.e. other than accommodation rooms) outside air for ventilation shall be introduced via the A/C systems to ensure the air being introduced into the building can be pre-treated to reduce humidity levels where required.

For accommodation rooms, the ventilation rates are relatively low. Condensation will be managed by separation of the infiltration source (typically via the entrance door and/or windows) from the A/C unit. To achieve this, the wall mounted indoor A/C unit is proposed to be located on the opposite side of the room to external doors and windows.





7.4 Mechanical Services Example Systems






7.4.1 Air Conditioning – High Occupancy / High Capacity Areas


System	Stantec Comment	Typical Spatial	Appearance
Multiple Indoor Units to Single Outdoor Unit (Multi-Head or Variable Refrigerant Volume) – Outdoor Unit			
Proposed system	Air Cooled Ducted Packaged Units	High capacity systems for large areas High sound levels Require dedicated plant area – recommended to be at ground level and screened for protection during cyclone event)	2m x 3m footprint 1.5m high Typically, 1m access off one side and rear of the unit. May also need additional space in front for duct connections pending plantroom layouts.
Grilles for Ducted Unit			
Proposed system	Swirl Diffuser	Ceiling Mounted Relatively flexible Provides high level of air distribution Recommended	
Alternative system	Linear Slot Diffuser	Limited Airflow Ceiling Mounted	
Alternative system	Square Pattern Diffuser	Ceiling Mounted	

System		Stantec Comment	Typical Spatial	Appearance
Alternative system	Wall Register	Wall Mounted		
Controller				
Proposed system	Central Controller	<p>Recommended for office and common areas</p> <p><u>Pros:</u></p> <p>Capability to control all fan coil units.</p> <p>Provide time scheduling, remote temperature adjustment and is centrally located for ease of access by authorised personnel and maintenance technicians.</p> <p><u>Cons:</u></p> <p>Additional costs to install and commission</p>		
Proposed system	Standard Wall Controller	<p>Recommended for office and common areas_ Located within each area for local user control.</p> <p><u>Pros:</u></p> <p>Provide occupant control: temperature, ON/OFF and fan speed, which may be set within limits via the central controller.</p> <p><u>Cons:</u></p> <p>One per fan coil unit wall mounted in area served.</p>		
Alternative system	Local Push Button	<p><u>Pros:</u></p> <p>Simplified local control to prevent any changes</p> <p><u>Cons:</u></p> <p>Occupants have On/Off Control Only</p> <p>Requires additional controls cost given that proprietary controller still required for maintenance</p>		





7.4.2 Air Conditioning – Large Office and Common Areas



System	Stantec Comment	Typical Spatial	Appearance
Multiple Indoor Units to Single Outdoor Unit (Multi-Head or Variable Refrigerant Volume) – Outdoor Unit			
Proposed system	Heat recovery	<p>Simultaneous Heating and Cooling for Separate Indoor Units</p> <p>1.25m x 800mm footprint</p> <p>1.8m high</p> <p>Typically requires 1m access of front of unit and 300mm off rear of unit. Must be able to access both sides but multiple units can be installed adjacent to each other.</p>	
Multiple Indoor Units to Single Outdoor Unit (Multi-Head or Variable Refrigerant Volume) – Indoor Units			
Proposed system	In ceiling ducted Unit	<p>Requires Clear void within the ceiling</p> <p>Can provide Outside Air</p> <p>Future Flexibility</p> <p>Recommended for office areas and public spaces</p>	<p>250 – 400mm deep</p> <p>700 – 1500mm wide</p> <p>900mm long</p> <p>All units require min 600mm clear access within ceiling void off one side as well as 600mm square ceiling access panel</p> 
Alternative system	Under Ceiling Mounted Unit	<p>Requires Clear Space under Ceiling</p> <p>Limited Ability to provide Outside Air</p> <p>Limited Future Flexibility</p>	<p>200mm deep</p> <p>900 – 1500 wide</p> <p>600mm long</p> <p>No additional access provisions – maintained from within the space</p> 
Alternative system	Cassette Unit	<p>Requires Clear Space within Ceiling Void</p> <p>Limited Ability to provide Outside Air</p> <p>Limited Future Flexibility</p>	<p>900mm square</p> <p>300mm high</p> <p>Requires 600mm square access panel adjacent unit</p> 

System	Stantec Comment	Typical Spatial	Appearance
Grilles for Ducted Unit			
Proposed system	Swirl Diffuser Ceiling Mounted Relatively flexible Provides high level of air distribution Recommended	Nominally 500mm diameter	
Alternative system	Linear Slot Diffuser Limited Airflow Ceiling Mounted	Typically 1200mm long and 120mm wide (2 slots) But can be custom length and can have additional slots depending on air flow	
Alternative system	Square Pattern Diffuser Ceiling Mounted	Nominally 600mm square	
Alternative system	Wall Register Wall Mounted	Custom sizes	
Controller			
Proposed system	Central Wall Controller Recommended for office and common areas <u>Pros:</u> Capability to control all fan coil units. Provide time scheduling, remote temperature adjustment and is centrally located for ease of access by authorised personnel and maintenance technicians. <u>Cons:</u> Additional costs to install and commission		



System		Stantec Comment	Typical Spatial	Appearance
Proposed system	Standard Wall Controller	<p>Recommended for office and common areas_ Located within each area for local user control.</p> <p><u>Pros:</u></p> <p>Provide occupant control: temperature, ON/OFF and fan speed, which may be set within limits via the central controller.</p> <p><u>Cons:</u></p> <p>One per fan coil unit wall mounted in area served.</p>		
Alternative system	Local Push Button	<p><u>Pros:</u></p> <p>Simplified local control to prevent any changes</p> <p><u>Cons:</u></p> <p>Occupants have On/Off Control Only</p> <p>Requires additional controls cost given that proprietary controller still required for maintenance</p>		

7.4.3 Air Conditioning – Accommodation and Small Standalone Areas






SYSTEM	Stantec Comment	Typical Spatial	Appearance
Single Split System - Outdoor Services			
Proposed system	Slimline Outdoor Units	Limited Maximum Capacity Only Available in Heat Pump	900mm wide 300mm deep 1000mm high (small - shown in adjacent image – proposed for accommodation modules) 1600mm high (large – may be used for other standalone spaces pending heat loads)
			
Single Split System - Indoor Units			
Proposed system	Wall Mounted Unit	Low cost Requires Space on Wall Limited Ability to provide Outside Air Limited Future Flexibility Recommended for accommodation rooms	900mm wide 300mm high 200mm deep
			
Alternative system	Under Ceiling Mounted Unit	Requires Clear Space under Ceiling Limited Ability to provide Outside Air Limited Future Flexibility	200mm deep 900 – 1500 wide 600mm long No additional access provisions – maintained from within the space
			
Alternative system	Cassette Unit	Requires Clear Space within Ceiling Void Limited Ability to provide Outside Air Limited Future Flexibility	900mm square 300mm high Requires 600mm square access panel adjacent unit
			


SYSTEM		Stantec Comment	Typical Spatial	Appearance
Controller				
Proposed system	Standard Wall Controller	<p>Recommended for office and common areas, Located within each area for local user control.</p> <p><u>Pros:</u></p> <p>Provide occupant control: temperature, ON/OFF and fan speed, which may be set within limits via the central controller.</p> <p><u>Cons:</u></p> <p>One per fan coil unit wall mounted in area served.</p>		
Proposed system	Standard Wireless Controller	<p>Recommended for accommodation rooms</p> <p><u>Pros:</u></p> <p>Provide occupant control: temperature, ON/OFF and fan speed, which may be set within limits via the central controller.</p> <p><u>Cons:</u></p> <p>Portable controller can be misplaced.</p> <p>Requires battery changes</p>		

7.4.4 Ventilation – Outside Air Systems



System	Stantec Comment	Typical Spatial	Appearance
Bathroom Exhaust Fans			
Possible system	In Ceiling Heat recovery Ventilator	Pre-Conditions Outside Air Require access on both sides for maintenance	1000m long 350mm high 700mm wide Requires 600mm clear ceiling void on both sides of the unit as well as 600 square ceiling access panel on both sides
Possible system	Direct Connection Roof Cowl	Requires Roof Cowl/wall grille to be located in close proximity of Fan Coil Unit. Only Suitable Ducted Fan Coil Units	
Possible system	In-Line Booster Fan	Suitable for small amounts of Outside Air.	250mm diameter (small systems) 600mm diameter (large systems) Requires ceiling access panel below
Controls			
Proposed system	Interlocked with A/C	Typical configuration to ensure outside air system runs automatically. This assumes that A/C will be on when area is occupied	

7.4.5 Ventilation – Exhaust

System		Stantec Comment	Typical Spatial	Appearance
BATHROOM EXHAUST FANS				
Proposed system	Inline Ducted Fan	Requires ceiling Void Protected from cyclone event	200 diameter (stand alone toilet or similar) 600 diameter (toilet block or similar) Requires ceiling access panel below	
Alternative system	Roof Mounted Fan	Requires Roof access Vulnerable to cyclone event	600mm square 800mm high	
Alternative system	Header Box Fan	Higher Noise Level than ducted. Limited Capacity Suitable for Ensuite applications	300mm square 250mm high No additional access	
Grilles for Ducted Fan				
Proposed system	Half Chevron	Easy to clean. Typically Aesthetically preferred		
Alternative system	Circular Adjustable Diffuser	Larger grille Adjustable from within space. Plastic Construction		

System		Stantec Comment	Typical Spatial	Appearance
Alternative system	Egg Crate	Difficult to Clean Allows Line of Sight through Grille		
Controls				
Proposed system	Switched with Lights	Typical configuration to associated fan use with occupancy (coupled with motion sensors and run-on timer) Recommended for public areas		
Alternative system	Switched Power Supply	Requires users to operate Recommended for Ensuites		


7.4.6 Ventilation – Commercial Kitchen Exhaust

System		Stantec Comment	Typical Spatial	Appearance
Commercial Kitchen Exhaust Fans				
Proposed System	Adjustable Pitch Axial Fan – Duct mounted	High Noise Level requires attenuation	800mm diameter	
		Located within ceiling void or plantroom to protect from cyclone event	Ceiling access panel required adjacent	
Alternative system	Roof Mounted Exhaust Fans	Roof access required, Cannot be attenuated externally – requires screens Vulnerable to cyclone event	1000mm square 1000mm high	

Appendix A – Electrical Drawings

ELECTRICAL SERVICES INTAKE INFRASTRUCTURE AND PRELIMINARY DISTRIBUTION

1 2 3 4 5



SITE INTAKE POWER SUBSTATION


PERMANENT GENERATOR
(60-80% OF FULL SITE LOAD)
4790 mm L x 1950 mm W x
2660 mm H

P P
DISTRIBUTION PITS


SOLE USE TRANSFORMER
4500 mm L x 3600 mm W
SUBSTATION TO BE LOCATED 6M AWAY FROM THE NEAREST FIRE PAVING REQUIREMENTS.

SMSB (APPROX)
4500 mm W x 1200 mm D
x 2200 mm H

INTAKE HORIZON POWER RING MAIN UNIT ON LOT BOUNDARY



INTAKE HORIZON POWER SOLE USE SUBSTATION AS SHOWN ON PLAN



MAIN DISTRIBUTION BOARD - 1000 x 600 x 2200 H

<p>Title SITE PLAN ELECTRICAL SERVICES</p>	<p>Client/Project ROWE GROUP ONSLow TOWNSHIP VILLAGE</p>	<p>Client/Project Logo miti creative</p>	<p>Notes</p>	<p>Issue Status PRELIMINARY FOR INFORMATION The document is subject to change for the use of the document for any other purpose is not permitted.</p>	<p>Revision By: [Signature] Date: [Date]</p>
<p>Project No. 301250498 Scale 1:1000</p>	<p>Drawn By: [Signature] Checked: [Signature] Date: [Date]</p>	<p>Copyright Reserved www.stantec.com This document is the property of Stantec Inc. and is not to be distributed outside the organization.</p>	<p>Stantec</p>	<p>Issue Status PRELIMINARY FOR INFORMATION The document is subject to change for the use of the document for any other purpose is not permitted.</p>	<p>Revision By: [Signature] Date: [Date]</p>

Appendix B - Hydraulic & Fire Drawings